



Lighting Your Life Since 1970

Product Specifications - 53211

|           |           |
|-----------|-----------|
| Job Name: | Job Type: |
| Quantity: | Comments: |

**53211**

**StarStrand 12" Super Star**

Brighter than Basic Star with 71 lumens per foot, and the added benefit of it being covered in a pliable clear plastic, StarStrand Super Star, a low voltage 12 volt system, excels in performance and durability. The plastic cover keeps dust and dirt from landing directly on the board and makes keeping it clean easy. Super Star is available in pre-manufactured lengths of 2 inches, 12 inches, 60 inches, 120 inches, and 240 inches with 4 pin connectors installed at each end for fast and sure installation. The maximum run is 50 feet. The black PC board is backed with 3M adhesive tape for easy installation. Optional dimming includes dimming from a wall or using a remote control. Applications for Super Star include cove and toe kick accent lighting, outdoor covered porches and patios, under cabinet lighting, step lighting, restaurant and lounges, and boats and recreation vehicles.



**Finish**

**Glass/Shade**

**Product Category**

LED Tape

**Lamping**

|                                   |                      |
|-----------------------------------|----------------------|
| <b>Number of Bulbs</b>            | 18                   |
| <b>Light Type</b>                 | LED                  |
| <b>Bulb Type</b>                  | LED                  |
| <b>Max Bulb Wattage</b>           | 0.16                 |
| <b>Max Fixture Wattage</b>        | 2.88                 |
| <b>Rated Life</b>                 | ±30,000 Hours        |
| <b>Rated Lumens</b>               | ±71                  |
| <b>Color Temp</b>                 | ±3,500 K             |
| <b>Bulb(s)</b>                    | Integrated           |
| <b>Light Up/Down</b>              | N/A                  |
| <b>Beam Spread</b>                | 120                  |
| <b>CRI</b>                        | 70-75                |
| <b>Photo Cell Included</b>        | N/A                  |
| <b>Ballast/Driver/Transformer</b> | No                   |
| <b>Dimmable</b>                   | Magnetic Low-Voltage |

**Measurements**

|                           |          |
|---------------------------|----------|
| <b>Width</b>              | 0.38"    |
| <b>Height</b>             | 0.09"    |
| <b>Length</b>             | 12.00"   |
| <b>Extension</b>          | N/A      |
| <b>Back Plate Width</b>   | N/A      |
| <b>Back Plate Height</b>  | N/A      |
| <b>HCO</b>                | N/A      |
| <b>Min Overall Height</b> | 0.00"    |
| <b>Max Overall Height</b> | N/A      |
| <b>Hanging Weight</b>     | 0.04 lbs |
| <b>Height Adjustable</b>  | N/A      |
| <b>Slope</b>              | N/A      |
| <b>Chain Length</b>       | N/A      |
| <b>Wire Length</b>        | N/A      |
| <b>Canopy Width</b>       | N/A      |
| <b>Canopy Height</b>      | N/A      |
| <b>Canopy Length</b>      | N/A      |

**Shipping**

|                           |           |
|---------------------------|-----------|
| <b>Carton Weight</b>      | 0.06 lbs  |
| <b>Carton Width</b>       | 1"        |
| <b>Carton Height</b>      | 1"        |
| <b>Carton Length</b>      | 13"       |
| <b>Carton Cubic Feet</b>  | 0.00      |
| <b>Master Pack</b>        | 200       |
| <b>Master Pack Weight</b> | 12.00 lbs |
| <b>Master Pack Width</b>  | 13.99"    |
| <b>Master Pack Height</b> | 11.42"    |
| <b>Master Pack Length</b> | 23.23"    |
| <b>Master Cubic Feet</b>  | 2.15      |
| <b>UPS Shippable</b>      | Yes       |

**Certification**

|                      |     |
|----------------------|-----|
| <b>Safety Rating</b> | Dry |
| <b>Energy Star</b>   | No  |
| <b>CA Title 24</b>   | No  |
| <b>CA Title 20</b>   | No  |
| <b>ADA</b>           | No  |
| <b>Dark Sky</b>      | N/A |

**Other**

|                          |              |
|--------------------------|--------------|
| <b>UPC Code</b>          | 783209068841 |
| <b>Shades Included</b>   | N/A          |
| <b>Crystals Included</b> | N/A          |
| <b>Diffuser Included</b> | N/A          |
| <b>Conversion Kit</b>    | N/A          |
| <b>Material</b>          | N/A          |

**Equivalents**

|                           |      |
|---------------------------|------|
| <b>Incandescent Watts</b> | 6.45 |
| <b>Fluorescent Watts</b>  | 1.42 |

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.

