

Lighting Your Life Since 1970

Product Specifications - 53552			
Job Name:	Job Type:		
Quantity:	Comments		



53552

Color Flex 24V 29-50K 60"

Glass/Shade

Product Category

LED Tape

Lamping		Measure
Number of Bulbs	90	Width
Light Type	LED	Height
Bulb Type	LED	Length
Max Bulb Wattage	0.16	Extension
Max Fixture Wattage	14.4	Back Pla
Rated Life	±30,000 Hours	
Rated Lumens	±0	HCO
Color Temp	2900-5000	
Bulb(s)	Integrated	
Light Up/Down	N/A	
Beam Spread	120	
CRI	70-75	Slope
Photo Cell Included	N/A	Chain Le
Ballast/Driver/Transformer	No	Wire Ler
Dimmable	No	Canopy
		Canany

Measurements	
Width	0.40"
Height	0.10"
Length	60.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	0.29 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	0.42 lbs
Carton Width	9"
Carton Height	1"
Carton Length	10"
Carton Cubic Feet	0.04
Master Pack	25
Master Pack Weight	11.24 lbs
Master Pack Width	11.03"
Master Pack Height	9.85"
Master Pack Length	25.20"
Master Cubic Feet	1.58
UPS Shippable	Yes

Certification		Other	Equivalents
	_		

Safety Rating	Dry	UPC Code	783209089150	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.