



Lighting Your Life Since 1970

Product Specifications - 87881SV

Job Name:	Job Type:
Quantity:	Comments:



87881SV
CounterMax MX-LD 1-Light LED
Add-On

Uses MXInterLink2 accessories. Click [here](#) for a complete list of compatible accessories.

Finish
 Silver

Glass/Shade

Product Category
 Under Cabinet Disc

Lamping

Number of Bulbs	24
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	.07
Max Fixture Wattage	1.7
Rated Life	±40,000 Hours
Rated Lumens	±130
Color Temp	±3,500 K
Bulb(s)	Integrated
Light Up/Down	N/A
Beam Spread	120
CRI	70-75
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

Measurements

Width	3.13"
Height	0.88"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	0.40 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Carton Weight	0.42 lbs
Carton Width	4"
Carton Height	2"
Carton Length	5"
Carton Cubic Feet	0.02
Master Pack	12
Master Pack Weight	5.95 lbs
Master Pack Width	9.45"
Master Pack Height	6.30"
Master Pack Length	10.43"
Master Cubic Feet	0.36
UPS Shippable	Yes

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

Other

UPC Code	783209064430
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Polycarbonate

Equivalents

Incandescent Watts	11.82
Fluorescent Watts	2.6

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.