


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:15inch	DIM.:	SERIAL No.:
MFR.: Libo	SUR.:φ0.078m	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 59.16 lm/W			
MODEL	57738WTBZ	I <sub>max</sub> (cd)	801.7	S/MH (C0/180)	1.26
NOMINAL POWER (W)	36	LOR (%)	100.0	S/MH (C90/270)	1.25
RATED VOLTAGE (V)	277	TOTAL FLUX (lm)	2184.0	h UP,DN (C0-180)	0.2,50.1
NOMINAL FLUX (lm)	2183.95	CIE CLASS	DIRECT	h UP,DN (C180-360)	0.3,49.4
LAMPS INSIDE	1	h up (%)	0.5	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120.0	h down (%)	99.5	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:Jack  
 Test Date:14 December 2017

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
 Humidity:65.0%  
 Test Distance:3.010m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	785.5	785.9	783.0	788.1	787.0	783.9	785.3	784.7	0~ 10	75.61	75.61	3.46,3.46
20	745.9	746.0	748.2	745.7	744.8	743.6	745.1	742.9	10~ 20	216.9	292.5	13.4,13.4
30	675.9	676.8	678.8	674.0	677.9	671.1	671.7	672.2	20~ 30	328.6	621.1	28.4,28.4
40	577.2	576.6	580.0	575.6	577.8	570.1	570.3	569.6	30~ 40	392.3	1013	46.4,46.4
50	454.2	454.9	458.9	453.2	456.1	446.2	447.9	445.3	40~ 50	396.8	1410	64.6,64.6
60	320.3	321.1	326.6	321.3	323.6	313.4	314.4	311.5	50~ 60	344.5	1755	80.3,80.3
70	189.1	189.6	194.3	190.5	192.3	182.9	183.3	180.4	60~ 70	249.4	2004	91.8,91.8
80	73.83	74.63	77.63	74.92	76.43	69.74	71.41	67.88	70~ 80	134.9	2139	97.9,97.9
90	3.071	3.054	3.120	3.419	3.425	3.536	4.103	3.770	80~ 90	33.81	2173	99.5,99.5
100	1.539	1.320	1.078	1.084	1.178	1.403	1.981	1.707	90~100	1.958	2175	99.6,99.6
110	1.762	1.561	1.399	1.395	1.431	1.487	1.715	1.604	100~110	1.506	2176	99.6,99.6
120	1.962	1.761	1.764	1.721	1.683	1.662	1.905	1.726	110~120	1.625	2178	99.7,99.7
130	2.023	1.936	1.971	1.940	1.843	1.817	1.997	1.872	120~130	1.650	2180	99.8,99.8
140	2.026	2.005	2.020	2.011	1.888	1.904	1.992	1.916	130~140	1.515	2181	99.9,99.9
150	1.992	1.991	1.959	2.003	1.900	1.889	1.948	1.883	140~150	1.237	2182	99.9,99.9
160	2.010	1.952	1.935	1.950	1.933	1.906	1.933	1.849	150~160	0.8943	2183	100,100
170	2.331	2.269	2.225	2.241	2.271	2.287	2.249	2.200	160~170	0.5753	2184	100,100
180	2.513	2.493	2.419	2.407	2.527	2.494	2.420	2.408	170~180	0.2211	2184	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:Jack  
 Test Date:14 December 2017

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
 Humidity:65.0%  
 Test Distance:3.010m [K=1.0000]  
 Remarks:

**UGR(Unified Glare Rating) Table**

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm											
NAME:					TYPE:			WEIGHT:			
SPEC.:15inch					DIM.:			SERIAL No.:			
MFR.: Libo					SUR.:φ0.078m			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	29.9	31.4	30.2	31.6	31.8	29.9	31.4	30.2	31.6	31.8	
	3H	31.2	32.6	31.5	32.8	33.1	31.2	32.6	31.5	32.9	33.1
	4H	31.7	33.1	32.1	33.3	33.6	31.8	33.1	32.1	33.3	33.6
	6H	32.1	33.3	32.4	33.6	33.9	32.1	33.4	32.5	33.6	33.9
	8H	32.2	33.4	32.5	33.7	34.0	32.2	33.4	32.6	33.7	34.0
	12H	32.2	33.4	32.6	33.7	34.0	32.3	33.4	32.6	33.7	34.0
4H	2H	30.4	31.7	30.7	32.0	32.3	30.4	31.7	30.7	32.0	32.3
	3H	32.0	33.1	32.3	33.4	33.7	32.0	33.1	32.3	33.4	33.7
	4H	32.6	33.6	33.0	34.0	34.3	32.6	33.7	33.0	34.0	34.3
	6H	33.1	34.0	33.5	34.3	34.7	33.1	34.0	33.5	34.4	34.7
	8H	33.2	34.1	33.6	34.4	34.8	33.2	34.1	33.7	34.5	34.9
	12H	33.3	34.1	33.7	34.5	34.9	33.3	34.1	33.8	34.5	34.9
8H	4H	32.8	33.7	33.2	34.0	34.4	32.8	33.7	33.2	34.1	34.5
	6H	33.4	34.1	33.9	34.5	35.0	33.4	34.1	33.9	34.6	35.0
	8H	33.6	34.3	34.1	34.7	35.1	33.7	34.3	34.1	34.7	35.2
	12H	33.8	34.3	34.3	34.8	35.3	33.8	34.3	34.3	34.8	35.3
12H	4H	32.8	33.6	33.3	34.0	34.4	32.8	33.6	33.3	34.0	34.4
	6H	33.4	34.1	33.9	34.5	35.0	33.5	34.1	33.9	34.5	35.0
	8H	33.7	34.2	34.2	34.7	35.2	33.7	34.3	34.2	34.7	35.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.3					+ 0.2 / - 0.2					


CIE Pub.117, 2184 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 2.7$ )

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:Jack  
 Test Date:14 December 2017

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
 Humidity:65.0%  
 Test Distance:3.010m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:15inch	DIM.:	SERIAL No.:
MFR.: Libo	SUR.:φ0.078m	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:Jack  
Test Date:14 December 2017

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
Humidity:65.0%  
Test Distance:3.010m [K=1.0000]  
Remarks:

### AAI Figure

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:15inch	DIM.:	SERIAL No.:
MFR.: Libo	SUR.:φ0.078m	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:Jack  
 Test Date:14 December 2017

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
 Humidity:65.0%  
 Test Distance:3.010m [K=1.0000]  
 Remarks:

### ISOLUX DIAGRAM

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:15inch	DIM.:	SERIAL No.:
MFR.: Libo	SUR.:φ0.078m	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: Jack  
 Test Date: 14 December 2017

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
 Humidity: 65.0%  
 Test Distance: 3.010m [K=1.0000]  
 Remarks:

### LED Avg.L Report

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:15inch	DIM.:	SERIAL No.:
MFR.: Libo	SUR.:φ0.078m	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	120866
L_0~180 (75) av	100109
L_0~180 (85) av	68631
L_90~270 (65) av	119921
L_90~270 (75) av	99242
L_90~270 (85) av	67151
L_45 (65) av	118310
L_45 (75) av	97079
L_45 (85) av	60250

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:Jack  
Test Date:14 December 2017

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
Humidity:65.0%  
Test Distance:3.010m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: Jack  
Test Date: 14 December 2017

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
Humidity: 65.0%  
Test Distance: 3.010m [K=1.0000]  
Remarks:



LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:15inch	DIM.:	SERIAL No.:
MFR.: Libo	SUR.:φ0.078m	Shielding Angle:

Table--1

UNIT: cd

C (DEG) g (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799
5	796	794	795	796	795	796	798	795	796	796	795	796	795	794	797	797	795	795	797
10	786	785	785	786	785	787	786	786	786	783	785	786	787	787	789	785	785	785	787
15	769	768	769	770	769	771	772	768	769	769	767	768	769	769	771	769	769	769	770
20	746	746	746	747	746	746	748	746	746	748	746	746	746	745	747	744	746	749	745
25	715	715	715	717	715	716	716	715	717	717	714	715	714	712	713	714	713	716	714
30	676	676	676	677	676	677	678	677	680	679	676	675	674	672	676	675	673	677	678
35	630	630	630	632	631	631	632	630	634	634	629	632	629	629	629	630	629	632	630
40	577	577	576	577	577	577	578	577	581	580	578	580	575	576	575	577	574	577	578
45	517	518	518	517	518	519	519	519	521	522	519	519	517	517	517	516	516	518	519
50	454	454	455	454	454	455	456	456	457	459	457	458	453	453	454	454	454	456	456
55	387	387	388	389	389	389	390	390	392	394	391	391	389	388	389	389	387	391	391
60	320	320	321	322	321	321	323	322	325	327	324	324	322	321	321	321	320	323	324
65	254	253	253	255	254	254	256	257	258	259	257	258	255	255	255	255	254	256	257
70	189	189	189	191	189	190	191	192	192	194	192	193	190	191	190	190	189	191	192
75	128	129	129	130	129	130	129	131	131	133	131	132	130	130	129	129	128	130	131
80	73.8	74.5	74.2	75.0	74.4	74.9	74.7	75.6	76.1	77.6	76.3	76.4	74.9	75.3	74.5	74.8	74.5	75.6	76.4
85	29.2	29.3	28.4	28.8	28.3	29.0	28.7	29.7	30.1	31.1	29.8	29.5	28.5	29.0	28.6	28.8	28.5	29.7	30.6
90	3.07	3.18	2.67	3.13	2.99	3.11	2.73	2.71	3.04	3.12	2.59	2.83	3.06	3.56	3.28	3.54	2.90	3.15	3.43
95	1.59	1.56	1.50	1.45	1.40	1.37	1.34	1.23	1.12	1.11	1.11	1.13	1.19	1.29	1.31	1.31	1.29	1.41	1.37
100	1.54	1.51	1.45	1.40	1.34	1.30	1.26	1.14	1.07	1.08	1.06	1.05	1.07	1.07	1.10	1.14	1.19	1.24	1.18
105	1.63	1.62	1.56	1.50	1.46	1.41	1.33	1.19	1.20	1.20	1.19	1.17	1.19	1.21	1.23	1.25	1.29	1.32	1.25
110	1.76	1.75	1.55	1.63	1.58	1.54	1.44	1.38	1.39	1.40	1.39	1.38	1.37	1.38	1.41	1.43	1.41	1.51	1.43
115	1.88	1.84	1.60	1.60	1.71	1.67	1.60	1.57	1.59	1.60	1.59	1.58	1.57	1.57	1.58	1.57	1.57	1.66	1.58
120	1.96	1.93	1.84	1.72	1.75	1.77	1.74	1.73	1.76	1.76	1.75	1.75	1.74	1.72	1.72	1.71	1.73	1.78	1.68
125	2.01	1.97	1.93	1.86	1.85	1.85	1.85	1.84	1.88	1.89	1.87	1.87	1.86	1.85	1.85	1.83	1.84	1.88	1.78
130	2.02	1.99	1.97	1.96	1.94	1.94	1.93	1.93	1.96	1.97	1.96	1.95	1.95	1.93	1.95	1.92	1.91	1.96	1.84
135	2.04	2.00	2.01	2.01	1.99	1.98	1.99	1.99	2.02	2.03	2.01	2.00	2.00	1.98	1.99	1.99	1.98	2.00	1.90
140	2.03	2.00	2.02	2.03	2.01	2.00	2.02	2.03	2.03	2.02	2.00	2.00	2.00	2.00	2.02	2.03	2.03	2.02	1.89
145	2.00	1.98	1.99	2.02	2.01	2.00	2.02	2.04	2.03	1.98	1.95	1.97	2.00	2.01	2.03	2.04	2.06	2.04	1.89
150	1.99	1.97	1.96	1.98	2.00	1.99	2.00	2.02	2.03	1.96	1.92	1.94	1.97	1.99	2.01	2.02	2.05	2.06	1.90
155	1.98	1.94	1.93	1.94	1.95	1.96	1.96	1.98	2.00	1.93	1.87	1.91	1.93	1.95	1.98	1.99	2.02	2.05	1.90
160	2.01	1.94	1.94	1.96	1.96	1.95	1.96	1.97	2.00	1.94	1.86	1.90	1.94	1.94	1.96	1.99	2.02	2.05	1.93
165	2.12	2.04	2.03	2.06	2.06	2.05	2.04	2.04	2.06	2.03	1.94	1.96	2.03	2.05	2.05	2.07	2.09	2.12	2.05
170	2.33	2.23	2.21	2.25	2.27	2.27	2.25	2.22	2.24	2.23	2.13	2.12	2.19	2.23	2.25	2.26	2.26	2.29	2.27
175	2.47	2.42	2.39	2.40	2.39	2.37	2.36	2.35	2.35	2.37	2.32	2.30	2.32	2.33	2.33	2.33	2.36	2.38	2.42
180	2.51	2.52	2.45	2.48	2.50	2.49	2.43	2.36	2.41	2.42	2.42	2.37	2.38	2.40	2.41	2.37	2.34	2.42	2.53

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:Jack  
Test Date:14 December 2017

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
Humidity:65.0%  
Test Distance:3.010m [K=1.0000]  
Remarks:

**LUMINOUS DISTRIBUTION INTENSITY DATA**

Test:U:276.97V I:0.1480A P:36.915W PF:0.9004 Freq:59.98Hz Lamp Flux:2183.95x1 lm																	
NAME:									TYPE:						WEIGHT:		
SPEC.:15inch									DIM.:						SERIAL No.:		
MFR.: Libo									SUR.:φ0.078m						Shielding Angle:		

**Table--2**
**UNIT: cd**

C (DEG) g (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799	799		
5	794	797	796	796	794	797	794	796	796	793	796	795	794	796	795	795	794		
10	784	783	786	784	784	787	784	786	785	782	785	783	783	786	787	784	787		
15	768	767	768	767	767	770	766	769	768	766	767	767	765	771	767	768	771		
20	744	744	743	746	742	745	742	742	745	742	742	743	743	743	743	744	747		
25	713	713	712	712	711	714	708	712	713	710	711	710	710	713	712	715	715		
30	673	672	670	672	670	673	669	671	672	672	670	671	672	672	673	674	678		
35	627	627	624	625	622	625	622	625	625	623	624	623	618	625	625	628	631		
40	574	573	570	571	569	571	570	572	570	569	568	569	568	571	571	574	578		
45	515	514	512	510	508	512	509	510	510	511	508	510	508	512	511	512	515		
50	452	451	448	448	445	447	445	447	448	446	445	445	443	448	447	450	452		
55	386	385	382	382	379	380	379	382	382	379	378	378	376	381	380	382	386		
60	319	318	315	315	312	313	312	314	314	313	311	310	310	313	312	316	318		
65	253	251	249	248	245	247	246	248	248	247	245	245	243	246	246	249	251		
70	188	187	184	184	182	184	182	184	183	183	181	181	179	182	181	184	187		
75	128	127	124	124	122	123	122	125	124	123	121	121	120	122	121	124	126		
80	73.6	72.7	71.0	70.4	69.1	69.6	69.5	71.5	71.4	70.5	68.6	68.4	67.4	68.4	68.1	70.3	72.2		
85	28.6	27.3	25.6	25.4	24.2	24.8	25.1	27.0	27.4	26.5	24.3	23.6	22.7	23.2	23.6	25.7	27.6		
90	3.40	3.03	3.10	3.50	3.57	3.39	3.19	3.99	4.10	4.11	3.59	3.82	3.87	3.67	3.12	2.76	2.83		
95	1.37	1.41	1.57	1.76	1.87	1.93	2.04	2.41	2.61	2.56	2.42	2.37	2.29	2.12	1.78	1.39	1.35		
100	1.18	1.22	1.30	1.36	1.44	1.54	1.65	1.78	1.98	1.99	1.93	1.85	1.77	1.64	1.49	1.27	1.26		
105	1.25	1.26	1.34	1.40	1.42	1.47	1.54	1.63	1.71	1.76	1.71	1.66	1.63	1.57	1.43	1.36	1.36		
110	1.42	1.40	1.44	1.47	1.50	1.56	1.60	1.67	1.72	1.73	1.71	1.67	1.64	1.57	1.48	1.49	1.49		
115	1.55	1.54	1.57	1.58	1.60	1.65	1.72	1.77	1.81	1.81	1.79	1.66	1.68	1.60	1.59	1.59	1.59		
120	1.66	1.66	1.68	1.68	1.64	1.67	1.82	1.87	1.91	1.88	1.84	1.75	1.73	1.72	1.69	1.67	1.69		
125	1.75	1.74	1.75	1.73	1.74	1.79	1.89	1.93	1.95	1.92	1.87	1.84	1.83	1.81	1.76	1.75	1.79		
130	1.83	1.81	1.80	1.81	1.83	1.91	1.95	1.99	2.00	1.98	1.95	1.92	1.89	1.86	1.84	1.82	1.86		
135	1.88	1.88	1.87	1.86	1.89	1.94	1.97	2.01	2.01	2.01	2.00	1.96	1.92	1.90	1.88	1.88	1.90		
140	1.91	1.93	1.92	1.91	1.90	1.94	1.96	1.98	1.99	2.03	2.03	1.99	1.93	1.90	1.89	1.88	1.87		
145	1.94	1.97	1.95	1.91	1.90	1.91	1.93	1.95	1.97	2.03	2.04	1.99	1.91	1.90	1.88	1.85	1.83		
150	1.96	1.97	1.94	1.89	1.88	1.90	1.91	1.92	1.95	2.02	2.01	1.95	1.89	1.87	1.83	1.83	1.81		
155	1.97	1.96	1.92	1.87	1.87	1.89	1.89	1.87	1.93	2.00	1.98	1.91	1.85	1.83	1.81	1.81	1.78		
160	1.99	1.98	1.93	1.91	1.91	1.93	1.89	1.85	1.93	2.00	1.97	1.90	1.85	1.85	1.84	1.81	1.78		
165	2.08	2.08	2.06	2.04	2.05	2.05	1.97	1.94	2.04	2.07	2.05	2.00	1.97	1.98	1.95	1.89	1.87		
170	2.29	2.27	2.28	2.30	2.27	2.23	2.14	2.15	2.25	2.25	2.22	2.21	2.22	2.18	2.13	2.07	2.08		
175	2.41	2.43	2.41	2.41	2.38	2.37	2.32	2.33	2.36	2.33	2.33	2.31	2.31	2.30	2.27	2.26	2.30		
180	2.51	2.46	2.48	2.50	2.48	2.43	2.35	2.41	2.42	2.42	2.36	2.38	2.41	2.41	2.37	2.35	2.42		

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:Jack  
 Test Date:14 December 2017

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.402  
 Humidity:65.0%  
 Test Distance:3.010m [K=1.0000]  
 Remarks: