Corona Fan | FANDELIGHT

61002

- · Includes One 6" Downrod
- · Includes Remote Control
- Title 20
- Color Tunable
- · Wifi Enabled







FCT6100WT (Remote Control)



FANDELIGHT™


Magnetically Connect to Wall Plate. Light Dimming. Battery Operated. *CCT funing on select SKU's

PRODUCT DESCRIPTION

Taking the standard fan to the next level, Fandelights such as this one house a Wifi-enabled fan within a decorative chandelier frame. This transitional look features a minimalistic frame finished in your choice of Matte Black or Satin Nickel and a downward directed ring of LED illumination. The Wi-Fi enabled functions control the light intensity, color temperature, and speed of the fan. They can be operated by the remote provided or popular Smart Home applications from your phone or other electronic device.

- · Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



MEASUREMENTS

: 27.5" D x 20" H **DIMENSION**

: 3 x 22" **BLADES** : 19.75" OAH MAX OAH

: 7.25" W x 2.75" H x 7.25" L CANOPY

HANGING WEIGHT : 15.9 lb

LAMPING

INPUT VOLTAGE : 120V

: 3,420 Rated (2,220 Del.) **LUMENS**

: 30W LED PCB Intergrated, 30W Total BULB

: By Control Provided DIMMABLE

: 80+ CRI CRI COLOR_TEMP : 2700-4000K

ENERGY INFORMATION AT HIGH SPEED

: 2600 CFM **AIRFLOW** : 20W **ELECTRICITY USE**

AIRFLOW EFFICIENCY: 130 CFM / W

FINISHES OPTION





MATERIAL

Aluminum+Steel+ABS

RATINGS

cETLus

Damp Location

INCLUDES

- Wall Mountable Remote Control
- 1 x 6" Downrod









DOWNROD OPTIONS • 18" (FRD0118BK, SN)

24" (FRD0124BK, SN)

30" (FRD0130BK, SN)
36" (FRD0136BK, SN)

ADDITIONAL

RATED LIFE: 35,000 Hours OPERATING TEMPERATURE: -20°

C (-4°F), 40°C (104°F)

LIGHTING DIRECTION: Down



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com