61022

- Dimmable only at 120V with Triac
- 80+ CRI
- Wifi Enabled





Job Name : _____ Job Type : _____ Quantity : __ Comments:



FCT6100WT (Remote Control)




FANDELIGHT™

Magnetically Connect to Wall Plate. Light Dimming. Battery Operated. *CCT tuning on select SKU's

PRODUCT DESCRIPTION


For those with smaller spaces in need of a fan, look no further than this Darling Fandelight. Eliminating the fan rod of a typical fandelight, this is the first hugger Fandelight that provides stylish trends with a low profile integrated fan. The combination finish of Natural Aged Brass, Matte Black, and the white fan blades make this a design that delivers trend, not just functionality. Fully dimmable and the Fandelight features can be controlled by the attractive remote provided or through its Wifi-enabled technology.



BLADE LUMENS ITEM# LAMPING DIMENSIONS RATED DEL WEIGHT BLADES **PTICH**

61022 120V, (4) x 7.25W, 29W Total, LED 3000K D24" X 10.5"H 3,400 2,200 19.4 lb (3) x ABS (Included) 12

Energy Information at High Speeds		
AIRFLOW CFM	AIRFLOW EFFICIENCY	ELECTRICITY USE
1130 CFM	50 CFM / W	22.6W



FINISHES: BLACK / NATURAL AGED BRASS (WTBKNAB) w/White Blades



White WT

MATERIAL

Steel + Aluminum Body **ABS Blades**

RATINGS

CETLUS Damp Location







ADDITIONAL

RATED LIFE 30000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com