

PRODUCT DESCRIPTION

Linear EE collection's commercial grade energy efficient lighting features linear frames of metal finished in Satin Nickel and White acrylic diffusers. High Power Factor ballasts allow for commercial applications and the fluorescent light source ensure low maintenance and energy cost savings. Specific styles of Linear EE are also available with a LED light source in the Linear LED collection.

37"

MEASUREMENTS

DIMENSION : 36" W x 6" H x 4" Ext

: 2.74" W x 35.17" H x 2.25" HCO **BACK PLATE**

HANGING WEIGHT : 6.02 lb

LAMPING

INPUT VOLTAGE : 120V

LUMENS : 4,300 Rated

BULB : 2 x 25W Fluorescent Med Bi Pin T8, 50W Total

BULB INCLUDED : (Not Included)

DIMMABLE : No

FINISHES OPTION



GLASS

White WT

MATERIAL

Metal

RATINGS

CETLUS Damp Location CA Title 24 ADA









INSTALL UP/DOWN: All **INCANDESCENT WATTS: 436 RATED LIFE 10000 Hours** OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com