BASIC-MAX | OUTDOOR CEILING FAN

89915

- Suitable for Wet Locations
- 12° +/- .5° Blade Pitch
- Remote Control Option (FCTHAND)
- **ABS Blades**
- Optional Light Kit FKT206 for Damp Locations
- 3 Speeds with Reverse



Optional Light Kits







Job Name : _____

Job Type : _ Quantity

Comments: _

BLADE FINISHES







BK w/Walnut/Pecan

FCTHAND


UNIVERSAL Wall Remote *Sold Separately Compatible with All Fans (Excl. Fandelights)





PRODUCT DESCRIPTION

The Basic-Max ceiling fan features the ability to be installed three different ways: close mount, standard stem, and optional stems up to 72" long.



| | | LUMENS | | | | | BLADE |
|-------|------------------------|----------------|-------|------|----------|--------------------|-------|
| ITEM# | LAMPING | DIMENSIONS | RATED | DEL | WEIGHT | BLADES | PTICH |
| 89915 | 120V, 4 X 9W LED 3000K | D52" X 18.25"H | 2100 | 1680 | 14.52 lb | 5 x ABS (Included) | 12 |

| Energy Information at High Speeds | | | | | | |
|-----------------------------------|--------------------|-----------------|--|--|--|--|
| AIRFLOW CFM | AIRFLOW EFFICIENCY | ELECTRICITY USE | | | | |
| 4779 CFM | 85 CFM / W | 37W | | | | |

1493 \$6

Always consult a qualified electrician before installing any lighting product.

FINISHES OPTION



BK: Black



OI: Oil Rubbed Bronze

MATERIAL

Steel

RATINGS

CETLUS Damp Location





FAN RODS: (SOLD SEPARATELY)

6" x 3 (Incl.)

12" (FRD18)

18" (FRD24) 24" (FRD30)

36" (FRD36)

48" (FRD48)

60" (FRD60)

72" (FRD72)

ADDITIONAL

OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

