


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 74.27 lm/W			
MODEL	RSZ200318513-10	Imax(cd)	315.1	S/MH(C0/180)	1.24
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	900.17	η UP,DN(C0-180)	0.8,48.9
NOMINAL FLUX(lm)	900.166	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.8,49.5
LAMPS INSIDE	1	η up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	98.4	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature:24.2DEG
Operators:East
Test Date:2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:44%
Test Distance:2.506m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	306.7	306.9	307.6	308.8	309.3	309.0	308.2	307.2	0- 10	29.71	29.71	3.3,3.3
20	286.2	286.1	288.3	290.3	290.8	290.1	289.2	287.9	10- 20	84.53	114.2	12.7,12.7
30	254.8	254.7	258.0	261.0	261.2	260.1	259.1	257.6	20- 30	126.5	240.7	26.7,26.7
40	216.1	215.4	219.8	222.9	222.8	221.6	221.1	219.3	30- 40	150.1	390.8	43.4,43.4
50	172.5	171.9	176.4	179.6	179.0	177.9	177.6	175.9	40- 50	153.2	544.0	60.4,60.4
60	126.8	126.3	130.5	133.4	133.3	132.2	132.0	130.1	50- 60	137.3	681.3	75.7,75.7
70	81.48	81.09	84.52	87.01	86.86	85.97	85.39	83.69	60- 70	106.1	787.4	87.5,87.5
80	41.68	41.31	43.51	45.69	46.25	45.75	44.87	43.32	70- 80	67.10	854.5	94.9,94.9
90	14.17	13.88	14.65	15.73	16.55	16.41	15.78	14.85	80- 90	31.04	885.6	98.4,98.4
100	0.3775	0.3479	0.2854	0.2342	0.1794	0.2462	0.2258	0.2660	90-100	6.805	892.4	99.1,99.1
110	0.7471	0.7312	0.6675	0.7041	0.4440	0.6285	0.6937	0.6823	100-110	0.4908	892.9	99.2,99.2
120	1.158	1.273	1.443	1.368	0.5683	1.165	1.417	1.071	110-120	0.9377	893.8	99.3,99.3
130	1.436	1.846	2.124	2.135	0.7969	1.740	1.941	2.128	120-130	1.336	895.1	99.4,99.4
140	1.416	2.579	2.742	2.462	1.045	2.021	2.195	2.351	130-140	1.548	896.7	99.6,99.6
150	2.223	2.866	3.110	2.782	1.089	2.439	2.540	2.578	140-150	1.443	898.1	99.8,99.8
160	2.722	2.846	2.935	2.931	1.484	2.548	2.526	2.128	150-160	1.142	899.3	99.9,99.9
170	2.545	2.702	3.155	2.619	1.273	2.510	2.655	1.049	160-170	0.7071	900.0	100,100
180	0.6763	0	1.272	0.0611	0.4208	0.4209	0.4240	0.4236	170-180	0.1854	900.2	100,100
DEG	LUMINOUS INTENSITY:cd Less than 25% Percent = 10.1 %									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: 10.0deg/s
 Temperature:24.2DEG
 Operators:East
 Test Date:2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity:44%
 Test Distance:2.506m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	26570	27667
80	21234	22165
75	20667	21540
70	21074	21862
65	21743	22459
60	22436	23090
55	23090	23700
50	23745	24276
45	24330	24864


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature:24.2DEG
Operators:East
Test Date:2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:44%
Test Distance:2.506m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.98	.94	1.00	.96	.92	.96	.92	.89	.91	.89	.86	.87	.85	.83	.81
2.0	.89	.82	.76	.87	.81	.75	.83	.78	.73	.80	.75	.71	.76	.73	.69	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.68	.63	.59	.56
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.44	.39	.49	.43	.39	.36
7.0	.51	.42	.36	.50	.41	.35	.48	.40	.35	.46	.40	.35	.45	.39	.34	.32
8.0	.46	.38	.32	.45	.37	.32	.44	.37	.31	.43	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.29	.42	.34	.28	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: 10.0deg/s
 Temperature:24.2DEG
 Operators:East
 Test Date:2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity:44%
 Test Distance:2.506m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm					
NAME: LED Ceiling Light			TYPE:N/A		WEIGHT:N/A
SPEC.:N/A			DIM.: N/A		SERIAL No.:N/A
MFR.: Maxim			SUR.:N/A		Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.327	.186	.059	.319	.182	.058	.305	.175	.056	.292	.168	.054	.279	.162	.052		
2.0	.300	.164	.050	.293	.161	.050	.280	.156	.048	.269	.151	.047	.258	.146	.046		
3.0	.274	.146	.044	.269	.144	.043	.257	.139	.042	.247	.135	.042	.237	.131	.041		
4.0	.252	.131	.038	.247	.129	.038	.237	.125	.037	.227	.122	.037	.219	.119	.036		
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032		
6.0	.215	.108	.031	.210	.106	.031	.202	.104	.030	.195	.101	.030	.188	.099	.029		
7.0	.199	.099	.028	.196	.097	.028	.188	.095	.027	.182	.093	.027	.176	.091	.027		
8.0	.186	.091	.026	.183	.090	.025	.176	.088	.025	.170	.086	.025	.165	.084	.025		
9.0	.174	.084	.024	.171	.083	.023	.165	.082	.023	.160	.080	.023	.155	.079	.023		
10.0	.164	.078	.022	.161	.078	.022	.156	.076	.021	.151	.075	.021	.146	.073	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.194	.168	.145	.166	.145	.125	.113	.099	.087	.065	.058	.050	.021	.019	.016	
2.0	.186	.144	.110	.159	.124	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.086	.153	.110	.075	.105	.076	.052	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.061	.100	.068	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.103	.060	.140	.089	.052	.096	.062	.037	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.052	.133	.082	.045	.092	.058	.032	.053	.034	.019	.017	.011	.006	
7.0	.148	.088	.046	.128	.076	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.071	.036	.084	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.077	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.063	.031	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature:24.2DEG
Operators:East
Test Date:2020-3-19

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:44%
Test Distance:2.506m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm										
NAME: LED Ceiling Light					TYPE:N/A			WEIGHT:N/A		
SPEC.:N/A					DIM.: N/A			SERIAL No.:N/A		
MFR.: Maxim					SUR.:N/A			Shielding Angle:N/A		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	23.5	25.0	23.7	25.2	25.4	23.6	25.1	23.9	25.3	25.5
3H	25.0	26.4	25.3	26.7	26.9	25.2	26.6	25.5	26.8	27.1
4H	25.7	27.0	26.0	27.3	27.6	25.9	27.2	26.2	27.5	27.8
6H	26.3	27.5	26.6	27.8	28.2	26.5	27.7	26.8	28.0	28.3
8H	26.6	27.8	26.9	28.1	28.4	26.7	28.0	27.1	28.3	28.6
12H	26.8	28.0	27.2	28.3	28.6	27.0	28.2	27.4	28.5	28.8
4H 2H	24.1	25.4	24.4	25.7	26.0	24.2	25.5	24.5	25.8	26.1
3H	25.8	27.0	26.2	27.3	27.6	25.9	27.1	26.3	27.4	27.8
4H	26.6	27.7	27.0	28.1	28.4	26.8	27.9	27.2	28.2	28.6
6H	27.4	28.3	27.8	28.7	29.1	27.5	28.5	28.0	28.9	29.3
8H	27.7	28.6	28.2	29.0	29.4	27.9	28.8	28.3	29.2	29.6
12H	28.1	28.9	28.5	29.3	29.7	28.2	29.1	28.7	29.5	29.9
8H 4H	27.0	27.8	27.4	28.2	28.7	27.1	28.0	27.5	28.4	28.8
6H	27.9	28.6	28.4	29.1	29.5	28.0	28.8	28.5	29.2	29.7
8H	28.4	29.0	28.8	29.5	30.0	28.5	29.2	29.0	29.6	30.1
12H	28.8	29.4	29.3	29.9	30.4	29.0	29.6	29.5	30.1	30.6
12H 4H	27.0	27.8	27.4	28.2	28.7	27.1	27.9	27.6	28.3	28.8
6H	28.0	28.7	28.5	29.1	29.6	28.1	28.8	28.6	29.3	29.7
8H	28.5	29.1	29.0	29.6	30.1	28.7	29.3	29.2	29.7	30.2
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.1 / - 0.3					+ 0.1 / - 0.2				

CIE Pub.117 Corrected 900.2 lm Total Lamp Luminous Flux.(8log(F/F0) = -0.4)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature:24.2DEG
Operators:East
Test Date:2020-3-19

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:44%
Test Distance:2.506m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	54	47	64	54	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	70	63	78	69	63	55
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	83	77	88	81	76	67
2.50	98	89	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	94	89	84	75
4.00	105	99	94	102	97	92	98	93	90	80
5.00	107	102	98	105	100	96	100	96	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004										
Suspended										
SHRNM = 1.25										

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: 10.0deg/s
 Temperature:24.2DEG
 Operators:East
 Test Date:2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity:44%
 Test Distance:2.506m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature: 24.2DEG
Operators: East
Test Date: 2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity: 44%
Test Distance: 2.506m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: 10.0deg/s
 Temperature:24.2DEG
 Operators:East
 Test Date:2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity:44%
 Test Distance:2.506m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature: 24.2DEG
Operators: East
Test Date: 2020-3-19

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity: 44%
Test Distance: 2.506m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180(65)av	22316
L_0~180(75)av	21527
L_0~180(85)av	28350
L_90~270(65)av	22535
L_90~270(75)av	21722
L_90~270(85)av	28360
L_45(65)av	22394
L_45(75)av	21588
L_45(85)av	28255

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature:24.2DEG
Operators:East
Test Date:2020-3-19

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:44%
Test Distance:2.506m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature: 24.2DEG
Operators: East
Test Date: 2020-3-19

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity: 44%
Test Distance: 2.506m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.0V I:0.1051A P:12.12W PF:0.9610 Lamp Flux:900.166x1 lm		
NAME: LED Ceiling Light	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	315	315	315	314	315	315	315	314	315	315	315	314	315	315	315	314			
5	312	313	313	312	313	313	313	313	314	314	314	313	313	313	312	312			
10	307	307	307	307	308	308	309	309	309	309	309	308	308	308	307	307			
15	298	298	298	299	300	300	301	301	301	302	301	301	300	300	299	298			
20	286	286	286	287	288	289	290	291	291	290	290	290	289	289	288	287			
25	272	271	272	273	274	276	277	277	277	277	276	276	275	275	274	273			
30	255	254	255	256	258	260	261	261	261	261	260	260	259	259	258	256			
35	236	236	236	237	240	242	243	243	243	242	242	241	241	241	239	238			
40	216	215	215	217	220	222	223	223	223	222	222	221	221	221	219	218			
45	194	194	194	196	199	201	202	202	201	201	200	200	200	199	198	196			
50	173	171	172	174	176	179	180	180	179	178	178	178	178	177	176	174			
55	150	149	149	151	154	156	157	157	156	156	155	155	155	154	153	152			
60	127	126	126	128	131	133	133	134	133	133	132	132	132	132	130	128			
65	104	103	103	105	107	109	110	110	109	109	109	108	108	107	106	105			
70	81.5	80.7	81.1	82.6	84.5	86.2	87.0	87.2	86.9	86.3	86.0	85.8	85.4	84.6	83.7	82.5			
75	60.5	59.9	60.1	61.4	63.0	64.3	65.3	65.7	65.5	65.1	64.9	64.6	64.1	63.3	62.4	61.4			
80	41.7	41.2	41.3	42.5	43.5	44.6	45.7	46.1	46.2	46.0	45.8	45.4	44.9	44.1	43.3	42.6			
85	26.2	25.9	25.8	26.4	27.3	28.1	28.8	29.3	29.7	29.6	29.4	29.1	28.6	27.9	27.3	26.8			
90	14.2	13.9	13.9	14.2	14.7	15.2	15.7	16.2	16.5	16.5	16.4	16.2	15.8	15.3	14.8	14.8			
95	5.95	5.59	5.30	5.28	5.47	5.72	6.67	7.07	7.30	7.34	7.09	7.13	6.89	6.61	6.40	5.90			
100	0.38	0.38	0.35	0.32	0.29	0.26	0.23	0.28	0.18	0.24	0.25	0.22	0.23	0.25	0.27	0.29			
105	0.56	0.56	0.52	0.50	0.48	0.47	0.49	0.39	0.27	0.46	0.42	0.42	0.43	0.44	0.48	0.45			
110	0.75	0.76	0.73	0.76	0.67	0.76	0.70	0.66	0.44	0.68	0.63	0.59	0.69	0.62	0.68	0.69			
115	0.96	0.96	0.99	1.08	1.09	1.07	1.03	0.95	0.50	0.88	0.91	0.95	1.07	1.00	1.05	0.95			
120	1.16	1.15	1.27	1.43	1.44	1.44	1.37	1.22	0.57	1.08	1.16	1.33	1.42	1.41	1.07	1.13			
125	1.33	1.34	1.55	1.82	1.81	1.82	1.75	1.47	0.66	1.27	1.42	1.67	1.55	1.46	1.38	1.19			
130	1.44	1.54	1.85	2.23	2.12	2.10	2.14	1.77	0.80	1.37	1.74	2.09	1.94	1.92	2.13	1.06			
135	1.53	1.74	2.24	2.35	2.42	2.38	2.36	2.13	0.95	1.51	2.09	2.30	2.17	2.27	2.14	2.03			
140	1.42	1.94	2.58	2.47	2.74	2.61	2.46	2.47	1.05	1.75	2.02	2.35	2.20	2.30	2.35	2.43			
145	1.67	2.16	2.87	2.69	2.92	2.81	2.63	2.72	1.06	1.70	2.47	2.05	1.87	1.69	2.52	2.62			
150	2.22	2.34	2.87	2.88	3.11	3.09	2.78	2.85	1.09	1.95	2.44	2.48	2.54	1.32	2.58	2.62			
155	2.58	2.52	2.82	2.98	3.06	3.04	2.87	2.97	1.30	1.95	2.10	2.49	2.64	1.45	2.27	2.30			
160	2.72	2.65	2.85	3.08	2.94	2.91	2.93	2.51	1.48	2.33	2.55	2.16	2.53	2.35	2.13	1.90			
165	2.83	2.46	2.87	3.26	3.02	2.98	3.05	2.61	1.46	2.08	2.59	2.49	2.35	1.79	1.59	2.51			
170	2.54	1.73	2.70	2.31	3.16	3.28	2.62	2.84	1.27	1.35	2.51	2.65	2.65	2.51	1.05	2.75			
175	1.44	1.82	2.07	1.68	1.80	1.98	2.09	2.47	2.06	2.01	1.42	1.63	1.90	1.36	0.95	1.40			
180	0.68	0.60	0.00	1.63	1.27	0.74	0.06	0.00	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: 10.0deg/s
Temperature:24.2DEG
Operators:East
Test Date:2020-3-19

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:44%
Test Distance:2.506m [K=1.0000]
Remarks: