


LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 37.89 lm/W
MODEL	LED	Imax(cd)	104.3	S/MH(C0/180)	0.95	
NOMINAL POWER(W)	2*4.5	LOR(%)	100.0	S/MH(C90/270)	0.88	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	405.41	h UP,DN(C0-180)	24.0,25.0	
NOMINAL FLUX(lm)	202.706	CIE CLASS	DIFFUSE	h UP,DN(C180-360)	25.7,25.2	
LAMPS INSIDE	2	h up(%)	49.7	CIBSE SHR NOM	1.00	
TEST VOLTAGE(V)	120.4	h down(%)	50.3	CIBSE SHR MAX	1.05	



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:30DEG
Operators:WCZ
Test Date:2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity:65.0%
Test Distance:6.220m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
5	102.9	99.72	98.82	100.0	103.5	100.4	99.22	99.96	0- 5	2.434	2.434	0.60,0.60
10	99.18	94.23	93.30	94.66	100.2	95.47	94.10	94.58	5- 10	6.990	9.424	2.32,2.32
15	92.75	87.93	87.79	88.17	93.98	89.55	88.98	88.33	10- 15	10.94	20.36	5.02,5.02
20	83.36	80.95	76.27	80.87	84.47	82.65	77.67	81.32	15- 20	13.96	34.32	8.47,8.47
25	71.50	70.08	64.75	69.64	72.26	71.69	66.35	70.55	20- 25	15.62	49.94	12.3,12.3
30	58.48	58.86	53.23	58.20	58.62	60.40	55.04	59.58	25- 30	15.98	65.92	16.3,16.3
35	46.68	48.58	48.58	47.71	45.67	50.18	49.50	49.59	30- 35	15.47	81.39	20.1,20.1
40	38.24	40.18	43.94	39.22	36.19	41.71	43.96	41.40	35- 40	14.78	96.17	23.7,23.7
45	31.60	35.15	39.29	34.02	29.67	36.13	38.42	36.30	40- 45	14.07	110.2	27.2,27.2
50	27.17	31.40	35.55	30.06	25.01	31.84	34.55	32.46	45- 50	13.36	123.6	30.5,30.5
55	23.99	27.98	31.80	26.86	21.84	28.27	30.69	28.97	50- 55	12.72	136.3	33.6,33.6
60	21.19	25.06	28.06	24.22	19.36	25.04	26.83	25.63	55- 60	12.04	148.4	36.6,36.6
65	18.38	22.48	25.77	21.91	16.93	22.14	24.76	22.53	60- 65	11.29	159.7	39.4,39.4
70	15.57	20.39	23.48	20.05	14.51	19.90	22.70	20.08	65- 70	10.58	170.2	42.4,42.4
75	10.07	18.74	21.19	18.56	9.345	18.34	20.63	18.41	70- 75	9.674	179.9	44.4,44.4
80	7.601	17.14	18.90	17.11	7.120	16.92	18.57	16.89	75- 80	8.552	188.5	46.5,46.5
85	5.644	15.60	16.61	15.71	5.302	15.62	16.50	15.48	80- 85	7.924	196.4	48.4,48.4
90	8.012	14.10	14.32	14.35	4.247	14.40	14.43	14.13	85- 90	7.384	203.8	50.3,50.3
95	4.814	15.54	16.38	15.74	5.425	15.65	16.61	15.24	90- 95	7.331	211.1	52.1,52.1
100	6.512	17.04	18.44	17.16	7.175	16.96	18.78	16.46	95-100	7.830	218.9	54.5,54.5
105	11.62	18.60	20.50	18.61	10.49	18.39	20.95	17.88	100-105	8.683	227.6	56.1,56.1
110	14.03	20.21	22.56	20.08	15.44	19.97	23.13	19.71	105-110	9.733	237.3	58.5,58.5
115	16.62	22.35	24.62	21.87	18.26	22.44	25.30	23.03	110-115	10.52	247.9	61.1,61.1
120	19.34	25.07	26.68	24.08	21.05	25.63	27.47	27.13	115-120	11.32	259.2	63.9,63.9
125	22.19	28.02	30.24	26.53	23.59	28.95	31.91	31.80	120-125	12.18	271.4	66.9,66.9
130	25.47	31.51	33.81	29.61	24.98	31.81	36.34	35.74	125-130	12.88	284.2	70.1,70.1
135	29.93	35.37	37.37	33.10	30.49	35.10	40.77	39.68	130-135	13.46	297.7	73.4,73.4
140	36.50	39.23	41.77	37.56	36.75	41.28	46.32	44.01	135-140	14.10	311.8	76.9,76.9
145	45.59	46.57	46.17	45.11	44.82	49.96	51.86	52.25	140-145	14.71	326.5	80.5,80.5
150	55.71	55.57	50.57	54.43	56.57	59.75	57.40	62.31	145-150	15.21	341.7	84.3,84.3
155	68.14	65.21	60.32	64.57	69.97	70.67	68.34	73.16	150-155	15.57	357.3	88.1,88.1
160	79.15	74.49	70.06	74.40	82.42	81.48	79.27	83.54	155-160	15.12	372.4	91.9,91.9
165	87.49	81.07	79.81	81.33	92.02	88.61	90.21	89.41	160-165	13.45	385.9	95.2,95.2
170	92.88	87.12	85.67	87.61	98.30	94.57	94.25	94.52	165-170	10.51	396.4	97.8,97.8
175	96.05	92.55	91.54	92.96	101.6	99.07	98.29	98.77	170-175	6.704	403.1	99.4,99.4
180	97.41	97.41	97.41	97.41	102.3	102.3	102.3	102.3	175-180	2.331	405.4	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:30DEG
 Operators:WCZ
 Test Date:2015-09-09

g Range: 0 - 180DEG
 g Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
 Humidity:65.0%
 Test Distance:6.220m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.07	1.07	1.07	.99	.99	.99	.83	.83	.83	.69	.69	.69	.56	.56	.56	.50
1.0	.92	.88	.84	.85	.81	.78	.71	.69	.66	.59	.57	.55	.48	.47	.45	.40
2.0	.80	.74	.68	.74	.68	.63	.62	.58	.55	.52	.49	.46	.42	.40	.38	.33
3.0	.70	.63	.57	.65	.59	.53	.55	.50	.46	.46	.42	.39	.37	.35	.32	.28
4.0	.63	.54	.48	.58	.51	.45	.49	.44	.39	.41	.37	.34	.34	.31	.28	.25
5.0	.56	.48	.42	.52	.45	.39	.44	.39	.34	.37	.33	.30	.31	.27	.25	.22
6.0	.50	.42	.36	.47	.40	.34	.40	.34	.30	.34	.29	.26	.28	.25	.22	.19
7.0	.46	.38	.32	.43	.35	.30	.37	.31	.27	.31	.27	.23	.26	.22	.20	.17
8.0	.42	.34	.29	.39	.32	.27	.34	.28	.24	.29	.24	.21	.24	.21	.18	.16
9.0	.38	.31	.26	.36	.29	.24	.31	.26	.22	.26	.22	.19	.22	.19	.17	.14
10.0	.35	.28	.23	.33	.26	.22	.29	.23	.20	.25	.20	.17	.21	.18	.15	.13



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 30DEG
 Operators: WCZ
 Test Date: 2015-09-09

g Range: 0 - 180DEG
 g Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.275
 Humidity: 65.0%
 Test Distance: 6.220m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

rcc	80%	70%	50%	30%	10%	0
rw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
rfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)					
0.0						
1.0	.311 .177 .056	.289 .165 .052	.248 .142 .045	.209 .121 .039	.174 .101 .033	
2.0	.276 .151 .046	.256 .141 .043	.218 .121 .038	.183 .103 .032	.151 .086 .027	
3.0	.249 .133 .040	.231 .124 .037	.197 .107 .032	.165 .090 .028	.135 .075 .023	
4.0	.228 .118 .035	.211 .110 .033	.179 .095 .028	.150 .081 .024	.123 .067 .020	
5.0	.209 .107 .031	.194 .100 .029	.165 .086 .025	.138 .073 .022	.113 .060 .018	
6.0	.194 .097 .028	.180 .091 .026	.153 .078 .023	.128 .066 .019	.104 .055 .016	
7.0	.180 .089 .025	.167 .083 .024	.142 .072 .021	.119 .061 .018	.097 .050 .015	
8.0	.168 .082 .023	.156 .077 .022	.133 .066 .019	.111 .056 .016	.091 .047 .014	
9.0	.157 .076 .021	.146 .071 .020	.125 .062 .017	.104 .052 .015	.085 .043 .012	
10.0	.148 .071 .020	.138 .066 .019	.117 .057 .016	.098 .049 .014	.080 .040 .012	

rcc	80%	70%	50%	30%	10%	0
rw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
rfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)					
0.0	.569 .569 .569	.487 .487 .487	.332 .332 .332	.191 .191 .191	.061 .061 .061	
1.0	.562 .538 .516	.481 .462 .444	.329 .318 .307	.189 .184 .179	.061 .059 .058	
2.0	.555 .517 .485	.475 .445 .419	.326 .308 .292	.188 .179 .171	.060 .058 .056	
3.0	.547 .501 .464	.469 .432 .402	.322 .300 .282	.186 .175 .166	.060 .057 .054	
4.0	.540 .489 .450	.463 .422 .391	.319 .294 .275	.184 .172 .163	.059 .056 .054	
5.0	.533 .480 .440	.458 .415 .383	.315 .290 .270	.183 .170 .160	.059 .056 .053	
6.0	.526 .472 .433	.452 .409 .377	.312 .286 .267	.181 .168 .159	.058 .055 .052	
7.0	.520 .466 .428	.448 .404 .373	.309 .283 .264	.180 .167 .157	.058 .055 .052	
8.0	.514 .461 .424	.443 .400 .369	.306 .280 .262	.178 .165 .156	.058 .054 .052	
9.0	.509 .456 .421	.438 .396 .367	.304 .278 .260	.177 .164 .155	.057 .054 .051	
10.0	.504 .452 .418	.434 .393 .365	.301 .276 .259	.176 .163 .155	.057 .054 .051	

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:30DEG
Operators:WCZ
Test Date:2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity:65.0%
Test Distance:6.220m [K=1.0000]
Remarks:

Uncorrected UGR Table

NAME: 86129					TYPE:					WEIGHT:				
DIM.:					SPEC.:					SERIAL No.:150909001				
MFR.: LCZ					SUR.:					PROTECTION ANGLE:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H	10.1	11.0	10.9	11.9	12.9	11.1	12.0	11.9	12.9	14.0				
3H	11.9	12.7	12.7	13.6	14.7	13.3	14.2	14.2	15.1	16.2				
4H	12.6	13.4	13.5	14.3	15.5	14.6	15.4	15.5	16.3	17.5				
6H	13.1	13.9	14.0	14.8	16.0	16.1	16.8	17.0	17.7	18.9				
8H	13.4	14.1	14.4	15.1	16.3	16.9	17.6	17.8	18.5	19.7				
12H	13.8	14.5	14.8	15.5	16.6	17.8	18.4	18.7	19.4	20.6				
4H 2H	10.8	11.6	11.7	12.5	13.7	11.6	12.4	12.5	13.3	14.4				
3H	12.9	13.6	13.9	14.5	15.7	14.1	14.7	15.0	15.7	16.9				
4H	13.9	14.5	14.9	15.5	16.7	15.5	16.2	16.5	17.1	18.3				
6H	14.5	15.1	15.5	16.1	17.3	17.2	17.7	18.2	18.7	20.0				
8H	15.0	15.5	16.0	16.5	17.7	18.1	18.6	19.1	19.6	20.9				
12H	15.6	16.1	16.6	17.1	18.3	19.1	19.6	20.1	20.6	21.9				
8H 4H	14.6	15.2	15.6	16.1	17.4	15.9	16.5	16.9	17.4	18.7				
6H	15.8	16.2	16.8	17.2	18.5	17.9	18.3	18.9	19.3	20.6				
8H	16.4	16.8	17.4	17.8	19.1	19.0	19.4	20.0	20.4	21.7				
12H	17.3	17.6	18.3	18.6	20.0	20.3	20.6	21.3	21.6	23.0				
12H 4H	14.8	15.3	15.8	16.3	17.6	16.0	16.5	17.0	17.5	18.7				
6H	16.2	16.6	17.2	17.6	18.9	18.1	18.4	19.1	19.4	20.8				
8H	17.1	17.4	18.1	18.4	19.7	19.3	19.6	20.3	20.6	22.0				
Variations with the observer position at spacings:														
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1								
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.2								
2.0H	+ 0.3 / - 0.4					+ 0.2 / - 0.3								

CIE Pub.117 Corrected 405.4 lm Total Lamp Luminous Flux.(8log(F/F0) = -3.1)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:30DEG
 Operators:WCZ
 Test Date:2015-09-09

g Range: 0 - 180DEG
 g Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
 Humidity:65.0%
 Test Distance:6.220m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	45	34	28	42	33	27	38	30	25	18
0.80	54	42	35	51	40	34	45	36	31	22
1.00	61	49	42	57	47	40	50	43	36	25
1.25	67	56	48	63	53	46	55	47	42	28
1.50	72	61	54	67	58	51	58	51	46	30
2.00	79	69	62	74	65	58	63	57	52	33
2.50	84	74	67	77	70	63	66	60	56	35
3.00	87	79	72	81	73	68	69	63	59	37
4.00	91	84	79	84	78	73	72	67	64	40
5.00	94	88	83	87	82	77	74	70	67	41
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004					Suspended			SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:30DEG
 Operators:WCZ
 Test Date:2015-09-09

g Range: 0 - 180DEG
 g Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
 Humidity:65.0%
 Test Distance:6.220m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:




C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:30DEG
Operators:WCZ
Test Date:2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity:65.0%
Test Distance:6.220m [K=1.0000]
Remarks:

AAI Figure

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 30DEG
Operators: WCZ
Test Date: 2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity: 65.0%
Test Distance: 6.220m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 30DEG
Operators: WCZ
Test Date: 2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity: 65.0%
Test Distance: 6.220m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 30DEG
Operators: WCZ
Test Date: 2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity: 65.0%
Test Distance: 6.220m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
0	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104
5	103	102	102	102	101	101	101	100	100.0	99.7	99.5	99.3	99.1	99.0	98.9	98.8	98.8	98.8	98.8
10	99.2	98.3	97.6	96.9	96.3	95.7	95.2	94.8	94.5	94.2	94.0	93.8	93.6	93.5	93.4	93.3	93.2	93.2	93.3
15	92.7	91.6	90.7	89.9	89.3	88.8	88.5	88.3	88.1	87.9	87.8	87.8	87.8	87.8	87.8	87.7	87.7	87.7	87.8
20	83.4	82.2	81.3	80.7	80.3	80.2	80.3	80.5	80.7	80.9	80.6	79.7	78.8	78.1	77.4	76.9	76.5	76.3	76.3
25	71.5	70.4	69.7	69.5	69.7	70.1	70.8	71.6	70.9	70.1	69.3	68.5	67.6	66.8	66.1	65.5	65.1	64.8	64.7
30	58.5	57.6	57.4	57.7	58.4	59.4	60.0	59.6	59.3	58.9	58.3	57.6	56.7	55.8	55.0	54.2	53.7	53.3	53.2
35	46.7	46.2	46.2	46.8	47.8	48.6	48.7	48.9	48.8	48.6	48.1	47.3	47.6	47.9	48.1	48.2	48.4	48.5	48.6
40	38.2	38.0	38.3	39.0	39.8	40.0	40.2	40.2	40.1	40.2	40.9	41.6	42.2	42.7	43.0	43.3	43.6	43.8	43.9
45	31.6	31.6	32.1	32.9	33.4	33.9	34.4	34.6	34.8	35.2	35.7	36.3	36.9	37.5	38.0	38.4	38.7	39.1	39.3
50	27.2	27.3	27.7	28.3	28.9	29.5	30.0	30.5	31.1	31.4	31.6	31.5	32.2	32.9	33.7	34.3	34.9	35.3	35.5
55	24.0	24.1	24.6	25.1	25.7	26.4	26.8	27.3	27.7	28.0	28.3	28.4	28.7	29.2	29.8	30.5	31.1	31.5	31.8
60	21.2	21.4	21.9	22.5	23.2	23.7	24.2	24.7	24.9	25.1	25.3	25.5	25.6	25.7	26.1	26.8	27.3	27.8	28.1
65	18.4	18.6	19.2	19.9	20.6	21.3	21.8	22.1	22.4	22.5	22.5	22.6	23.1	23.4	23.6	24.4	25.0	25.5	25.8
70	15.6	15.9	16.5	17.4	18.3	18.9	19.4	19.9	20.1	20.4	20.6	20.9	21.3	21.7	21.7	22.4	22.9	23.3	23.5
75	10.1	11.1	12.6	13.9	14.1	16.1	17.3	18.0	18.4	18.7	19.0	19.3	19.7	20.0	20.0	20.5	20.8	21.1	21.2
80	7.60	7.85	8.42	9.15	10.0	12.8	15.6	16.3	16.8	17.1	17.4	17.7	18.0	18.3	18.3	18.6	18.8	18.8	18.9
85	5.64	7.91	10.5	10.5	10.5	12.0	14.1	14.8	15.2	15.6	15.9	16.2	16.4	16.6	16.6	16.7	16.7	16.6	16.6
90	8.01	5.82	9.70	10.7	11.5	12.2	12.9	13.4	13.8	14.1	14.4	14.7	14.9	14.9	14.9	14.8	14.6	14.4	14.3
95	4.81	5.25	9.26	9.12	10.1	12.6	13.9	14.6	15.1	15.5	15.9	16.2	16.3	16.5	16.6	16.5	16.6	16.5	16.4
100	6.51	6.89	7.54	8.68	9.51	14.2	15.1	15.9	16.5	17.0	17.4	17.6	17.8	18.0	18.2	18.3	18.5	18.5	18.4
105	11.6	12.2	12.9	14.3	14.2	15.9	16.6	17.4	18.1	18.6	18.9	19.1	19.3	19.6	19.9	20.1	20.4	20.5	20.5
110	14.0	14.7	15.6	16.6	17.6	18.3	18.9	19.3	19.8	20.2	20.5	20.6	20.8	21.2	21.5	21.9	22.4	22.6	22.6
115	16.6	17.2	18.2	19.3	20.2	21.0	21.6	22.0	22.3	22.3	22.3	22.1	22.4	22.9	23.2	23.8	24.3	24.6	24.6
120	19.3	20.0	20.9	21.9	23.0	23.6	24.2	24.7	24.9	25.1	25.1	25.1	25.2	25.4	25.4	26.0	26.4	26.7	26.7
125	22.2	22.8	23.8	24.6	25.6	26.5	26.9	27.4	27.8	28.0	28.3	28.5	28.4	28.7	29.0	29.6	30.0	30.2	30.2
130	25.5	26.0	26.8	27.7	28.5	29.4	30.1	30.6	31.1	31.5	31.8	31.9	31.7	32.3	32.8	33.3	33.6	33.8	33.8
135	29.9	30.2	30.9	31.9	32.6	33.4	34.1	34.6	35.1	35.4	35.5	35.7	36.1	36.5	36.9	37.2	37.3	37.4	37.4
140	36.5	36.5	36.9	37.8	38.8	39.3	39.8	40.0	39.8	39.2	39.9	40.4	40.9	41.2	41.5	41.7	41.7	41.8	41.8
145	45.6	45.1	45.2	45.6	46.3	46.8	46.7	46.8	46.7	46.6	46.2	45.6	45.8	46.0	46.1	46.2	46.2	46.2	46.2
150	55.7	54.8	54.5	54.6	55.2	55.9	56.3	56.1	55.9	55.6	55.1	54.4	53.7	53.0	52.2	51.5	51.1	50.7	50.6
155	68.1	66.9	66.1	65.7	65.6	65.8	66.2	66.6	66.0	65.2	64.5	63.7	63.0	62.3	61.6	61.1	60.7	60.4	60.3
160	79.2	77.8	76.8	76.0	75.5	75.1	74.8	74.7	74.6	74.5	74.0	73.2	72.4	71.7	71.1	70.6	70.3	70.1	70.1
165	87.5	86.3	85.2	84.3	83.5	82.8	82.3	81.8	81.4	81.1	80.8	80.5	80.3	80.1	80.0	79.9	79.8	79.8	79.8
170	92.9	92.0	91.1	90.4	89.7	89.0	88.5	88.0	87.5	87.1	86.7	86.4	86.2	86.0	85.8	85.7	85.7	85.6	85.7
175	96.0	95.6	95.1	94.6	94.2	93.8	93.5	93.1	92.8	92.6	92.3	92.1	91.9	91.8	91.7	91.6	91.5	91.5	91.5
180	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4

C Range: 0 - 360DEG

C Interval: 5.0DEG

Test Speed: HIGH

Temperature:30DEG

Operators:WCZ

Test Date:2015-09-09

g Range: 0 - 180DEG

g Interval: 0.5DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275

Humidity:65.0%

Test Distance:6.220m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

Table--2

UNIT: cd

C(DEG) g (DEG)	95	100	105	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185
0	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104
5	98.8	98.9	98.9	99.0	99.2	99.3	99.5	99.8	100	100	101	101	101	102	102	103	103	103	103
10	93.3	93.3	93.4	93.5	93.7	93.9	94.1	94.4	94.7	95.0	95.4	95.9	96.4	97.0	97.7	98.4	99.3	100	99.4
15	87.8	87.7	87.8	87.9	87.9	87.9	88.0	88.1	88.2	88.4	88.7	89.0	89.5	90.1	90.8	91.7	92.7	94.0	92.9
20	76.3	76.5	77.0	77.5	78.1	78.8	79.6	80.5	80.9	80.6	80.5	80.4	80.5	80.7	81.2	82.0	83.1	84.5	83.3
25	64.8	65.1	65.5	66.1	66.8	67.5	68.3	69.0	69.6	70.3	71.0	70.3	69.8	69.5	69.5	70.0	70.9	72.3	71.1
30	53.3	53.7	54.2	54.9	55.7	56.4	57.2	57.7	58.2	58.5	58.7	58.8	58.3	57.5	57.0	57.0	57.5	58.6	57.8
35	48.6	48.5	48.4	48.1	47.7	47.2	46.7	47.4	47.7	47.8	47.7	47.4	47.0	46.3	45.4	44.9	45.0	45.7	45.2
40	44.0	43.9	43.5	43.1	42.5	41.8	41.0	40.1	39.2	39.0	38.7	38.4	37.9	37.5	36.8	36.2	36.0	36.2	36.1
45	39.4	39.2	38.7	38.1	37.4	36.5	35.6	34.7	34.0	33.3	32.9	32.8	32.3	31.7	31.1	30.2	29.7	29.7	29.7
50	35.6	35.2	34.6	33.8	32.7	31.7	30.7	30.4	30.1	29.7	29.4	28.9	28.2	27.5	26.7	26.0	25.3	25.0	25.2
55	31.8	31.4	30.7	29.8	28.8	28.1	27.4	27.1	26.9	26.6	26.3	25.9	25.5	24.8	23.9	23.1	22.3	21.8	22.0
60	27.9	27.5	26.9	26.0	25.2	25.0	24.6	24.4	24.2	24.1	24.0	23.6	23.1	22.7	21.6	20.7	19.9	19.4	19.5
65	25.6	25.2	24.5	23.5	22.8	22.5	22.0	21.9	21.9	21.8	21.7	21.4	20.9	20.2	19.5	18.3	17.5	16.9	17.1
70	23.4	23.1	22.4	21.6	21.2	20.9	20.4	20.2	20.0	19.8	19.6	19.2	18.2	17.9	16.8	15.9	15.0	14.5	14.7
75	21.1	20.9	20.5	19.9	19.6	19.3	18.9	18.8	18.6	18.2	17.8	17.0	13.5	13.3	11.4	10.4	9.64	9.35	9.51
80	18.9	18.8	18.6	18.2	18.1	17.8	17.5	17.4	17.1	16.8	16.3	14.6	11.6	9.80	10.7	9.45	7.95	7.12	7.39
85	16.7	16.7	16.7	16.6	16.5	16.4	16.2	16.0	15.7	15.3	14.9	13.3	11.7	10.6	11.3	10.3	7.55	5.30	5.62
90	14.4	14.6	14.8	15.0	15.0	15.0	14.8	14.6	14.4	14.0	13.6	13.0	12.4	11.6	10.7	9.46	5.21	4.25	5.95
95	16.4	16.5	16.5	16.5	16.4	16.3	16.1	16.0	15.7	15.4	14.8	14.2	12.7	10.4	9.31	8.98	5.46	5.43	7.47
100	18.4	18.3	18.1	17.9	17.8	17.6	17.5	17.4	17.2	16.8	16.2	15.5	14.3	9.94	8.80	7.82	7.30	7.18	7.82
105	20.4	20.2	19.8	19.4	19.2	18.9	18.8	18.7	18.6	18.3	17.8	17.1	16.3	14.3	14.7	13.2	11.9	10.5	12.5
110	22.4	22.1	21.5	20.9	20.7	20.3	20.2	20.1	20.1	19.9	19.6	19.1	18.6	17.8	17.0	16.0	15.2	15.4	16.0
115	24.4	24.0	23.3	22.4	22.3	21.8	21.5	21.7	21.9	21.9	21.7	21.4	20.9	20.3	19.6	18.5	17.8	18.3	18.8
120	26.4	26.0	25.4	24.6	24.5	24.1	24.0	24.0	24.1	24.1	23.9	23.6	23.2	22.8	21.9	21.0	20.4	21.1	21.5
125	30.0	29.6	28.9	28.1	27.5	26.9	26.8	26.7	26.5	26.4	26.2	26.0	25.7	24.9	24.2	23.5	22.9	23.6	24.0
130	33.5	33.1	32.5	31.7	30.8	30.0	29.7	29.8	29.6	29.5	29.1	28.8	28.2	27.4	26.8	26.1	25.6	25.0	25.8
135	37.1	36.8	36.3	35.7	35.1	34.5	33.8	33.6	33.1	33.0	32.8	32.4	31.8	31.1	30.5	29.7	29.3	30.5	30.3
140	41.6	41.3	41.0	40.6	40.1	39.5	38.9	38.2	37.6	37.4	37.5	37.3	37.0	36.6	35.9	35.2	34.9	36.7	36.6
145	46.0	45.9	45.7	45.4	45.1	44.7	44.4	44.8	45.1	45.1	44.8	44.5	44.1	43.4	42.6	42.2	42.3	44.8	44.5
150	50.6	50.8	51.2	51.8	52.4	53.0	53.6	54.1	54.4	54.6	54.7	54.8	54.2	53.3	52.8	52.6	53.0	56.6	55.7
155	60.4	60.6	60.9	61.5	62.0	62.7	63.3	63.9	64.6	65.1	65.7	65.1	64.6	64.4	64.4	64.7	65.4	70.0	68.9
160	70.1	70.3	70.7	71.2	71.8	72.5	73.2	74.0	74.4	74.3	74.3	74.4	74.6	74.9	75.4	76.1	77.1	82.4	81.3
165	79.8	79.9	80.0	80.2	80.4	80.6	80.8	81.1	81.3	81.7	82.0	82.5	83.0	83.6	84.3	85.3	86.3	92.0	91.0
170	85.7	85.8	85.9	86.1	86.3	86.6	86.9	87.2	87.6	88.0	88.5	89.0	89.6	90.3	91.0	91.8	92.6	98.3	97.6
175	91.6	91.6	91.7	91.8	92.0	92.2	92.4	92.7	93.0	93.3	93.6	94.0	94.4	94.8	95.2	95.7	96.2	102	101
180	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	102	102

C Range: 0 - 360DEG

C Interval: 5.0DEG

Test Speed: HIGH

Temperature:30DEG

Operators:WCZ

Test Date:2015-09-09

g Range: 0 - 180DEG

g Interval: 0.5DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275

Humidity:65.0%

Test Distance:6.220m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

Table--3

UNIT: cd

C(DEG) g (DEG)	190	195	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280
0	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104
5	103	102	102	102	101	101	101	100	100	100.0	99.8	99.6	99.5	99.4	99.3	99.2	99.2	99.2	99.2
10	98.6	98.0	97.4	96.9	96.5	96.1	95.8	95.5	95.2	95.0	94.8	94.7	94.5	94.4	94.3	94.2	94.1	94.0	94.0
15	92.0	91.3	90.7	90.3	89.9	89.7	89.6	89.6	89.5	89.5	89.4	89.4	89.3	89.3	89.2	89.1	89.0	88.9	88.8
20	82.4	81.9	81.6	81.6	81.7	81.9	82.3	82.6	82.3	81.6	80.7	80.0	79.3	78.7	78.2	77.9	77.7	77.6	77.7
25	70.5	70.3	70.6	71.1	71.8	72.7	72.2	71.7	71.1	70.4	69.7	68.9	68.2	67.5	67.0	66.6	66.4	66.3	66.4
30	57.5	57.9	58.7	59.8	60.6	60.6	60.6	60.4	60.1	59.5	58.8	58.0	57.2	56.5	55.8	55.3	55.0	55.0	55.2
35	45.4	46.1	47.4	48.4	49.1	49.6	50.1	50.2	50.0	49.4	49.6	49.8	49.9	49.9	49.8	49.7	49.5	49.3	49.2
40	36.5	37.3	38.3	39.0	39.9	40.6	41.2	41.7	42.6	43.3	43.8	44.1	44.3	44.4	44.3	44.1	44.0	43.8	43.7
45	30.2	31.2	32.0	32.9	33.8	34.5	35.2	36.1	36.9	37.7	38.2	38.6	38.8	38.8	38.8	38.6	38.4	38.3	38.2
50	25.7	26.4	27.3	28.3	29.4	30.3	31.1	31.8	32.3	32.5	33.2	33.8	34.3	34.6	34.7	34.7	34.6	34.4	34.2
55	22.5	23.1	24.0	25.0	25.7	26.6	27.5	28.3	28.9	29.1	29.7	30.0	30.4	30.7	30.8	30.8	30.7	30.6	30.4
60	19.9	20.6	21.5	22.1	22.8	23.6	24.3	25.0	25.7	26.2	26.6	26.5	26.7	26.9	27.0	26.9	26.8	26.8	26.6
65	17.5	18.3	18.9	19.6	20.3	20.9	21.5	22.1	22.7	23.3	24.0	24.1	24.2	24.6	24.8	24.8	24.8	24.7	24.5
70	15.3	15.6	16.7	16.7	18.0	18.5	19.1	19.9	20.7	21.4	22.1	22.3	22.3	22.6	22.8	22.7	22.7	22.7	22.5
75	10.1	10.9	12.5	12.5	15.2	16.9	17.6	18.3	19.0	19.7	20.3	20.5	20.4	20.7	20.7	20.6	20.6	20.7	20.6
80	9.34	11.2	9.81	11.4	13.2	15.6	16.3	16.9	17.5	18.1	18.5	18.8	18.7	18.7	18.7	18.6	18.6	18.6	18.6
85	8.79	11.2	10.9	11.7	12.8	14.5	15.1	15.6	16.1	16.5	16.9	17.0	16.9	16.8	16.7	16.5	16.5	16.6	16.7
90	9.86	10.7	11.5	12.3	12.9	13.5	14.0	14.4	14.8	15.0	15.2	15.2	15.1	14.9	14.7	14.4	14.4	14.6	14.8
95	10.6	9.03	10.4	12.9	13.9	14.5	15.1	15.6	16.1	16.5	16.8	16.9	16.8	16.7	16.7	16.5	16.6	16.7	17.0
100	8.27	9.23	10.0	14.2	15.0	15.7	16.3	17.0	17.6	18.1	18.4	18.5	18.5	18.5	18.7	18.7	18.8	18.9	19.1
105	13.6	14.7	14.8	15.8	16.3	17.0	17.7	18.4	19.1	19.7	19.9	20.3	20.2	20.3	20.7	20.8	21.0	21.1	21.3
110	16.4	17.1	17.9	18.4	18.7	18.9	19.2	20.0	20.8	21.3	21.5	22.1	21.8	22.1	22.8	22.9	23.1	23.3	23.5
115	19.4	20.1	20.8	21.3	21.7	21.9	22.1	22.4	22.8	23.0	23.2	23.9	23.6	24.1	24.9	25.0	25.3	25.5	25.6
120	22.2	23.0	24.0	24.2	24.5	25.0	25.3	25.6	25.9	25.8	25.8	26.4	26.1	26.5	27.1	27.2	27.5	27.7	28.0
125	24.7	25.4	26.3	27.1	27.5	28.0	28.5	29.0	29.0	28.2	29.3	30.3	30.6	31.0	31.5	31.7	31.9	32.1	32.4
130	26.9	27.8	28.6	29.7	30.9	31.3	31.5	31.8	31.8	31.5	33.4	34.6	35.1	35.6	36.0	36.1	36.3	36.5	36.8
135	30.4	30.9	32.2	33.7	34.4	34.5	34.6	35.1	36.2	37.6	38.8	39.7	39.9	40.4	40.5	40.6	40.8	41.0	41.3
140	37.0	37.9	38.8	39.2	39.3	39.4	39.7	41.3	42.7	43.6	44.6	45.2	45.5	45.9	46.0	46.2	46.3	46.5	46.7
145	44.6	45.2	46.2	46.9	47.3	48.2	49.3	50.0	50.0	49.9	50.4	50.8	51.2	51.4	51.6	51.7	51.9	52.0	52.2
150	55.5	55.9	56.6	57.8	58.8	59.3	59.5	59.7	59.8	59.6	59.2	58.8	58.4	57.9	57.5	57.4	57.4	57.6	58.1
155	68.4	68.3	68.6	69.2	70.0	71.1	70.9	70.7	70.4	70.0	69.7	69.3	69.0	68.6	68.4	68.3	68.3	68.5	68.8
160	80.5	80.0	79.8	79.8	80.0	80.4	80.9	81.5	81.5	81.0	80.6	80.1	79.8	79.5	79.3	79.2	79.3	79.4	79.6
165	90.2	89.5	89.0	88.7	88.6	88.5	88.5	88.6	88.8	89.0	89.2	89.4	89.5	89.8	89.9	90.1	90.2	90.3	90.2
170	96.9	96.4	95.9	95.5	95.2	94.9	94.7	94.6	94.4	94.3	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.3	94.2
175	101	101	100	100.0	99.7	99.5	99.3	99.1	98.9	98.8	98.6	98.5	98.4	98.4	98.3	98.3	98.3	98.3	98.3
180	102	102	102	102	102	102	102	102	102	102	102	102	102	102	102	102	102	102	102

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:30DEG
Operators:WCZ
Test Date:2015-09-09

g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity:65.0%
Test Distance:6.220m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 86129	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:150909001
MFR.: LCZ	SUR.:	PROTECTION ANGLE:

Table--4

UNIT: cd

C(DEG) g (DEG)	285	290	295	300	305	310	315	320	325	330	335	340	345	350	355				
0	104	104	104	104	104	104	104	104	104	104	104	104	104	104	104				
5	99.2	99.3	99.4	99.5	99.6	99.8	100.0	100	100	101	101	101	101	102	102				
10	94.0	94.0	94.1	94.1	94.3	94.4	94.6	94.8	95.1	95.5	95.9	96.4	97.0	97.6	98.4				
15	88.7	88.6	88.5	88.4	88.3	88.3	88.3	88.4	88.5	88.7	89.0	89.4	90.0	90.7	91.7				
20	78.0	78.4	78.9	79.5	80.2	81.1	81.3	80.9	80.6	80.4	80.3	80.4	80.7	81.3	82.2				
25	66.8	67.2	67.8	68.5	69.2	69.8	70.5	71.2	71.9	71.0	70.3	69.8	69.6	69.8	70.4				
30	55.7	56.3	57.0	57.8	58.5	59.1	59.6	59.9	60.1	60.3	59.7	58.6	57.9	57.5	57.7				
35	49.1	49.0	48.9	48.7	48.5	49.2	49.6	49.7	49.6	49.3	49.1	48.2	47.1	46.5	46.3				
40	43.6	43.5	43.3	43.0	42.6	42.1	41.4	41.2	41.3	41.1	40.8	40.4	39.5	38.7	38.2				
45	38.1	38.0	37.8	37.6	37.2	36.8	36.3	36.0	35.8	35.4	34.8	34.2	33.5	32.5	31.8				
50	33.9	33.6	33.2	32.7	32.4	32.6	32.5	32.1	31.6	31.1	30.4	29.7	29.1	28.3	27.6				
55	30.1	29.8	29.5	29.3	29.2	29.2	29.0	28.5	28.1	27.6	27.2	26.5	25.9	25.3	24.5				
60	26.3	26.0	26.2	26.3	26.2	25.9	25.6	25.3	25.1	24.6	24.2	23.9	23.1	22.5	21.8				
65	24.1	23.6	23.9	23.7	23.1	22.8	22.5	22.3	22.0	21.8	21.4	20.9	20.4	19.6	19.0				
70	22.2	21.9	22.1	21.8	21.3	20.7	20.1	19.5	19.2	19.0	18.6	18.2	17.5	16.8	16.2				
75	20.4	20.2	20.3	20.1	19.4	18.9	18.4	17.9	17.3	16.6	13.8	13.9	12.7	12.2	11.3				
80	18.6	18.5	18.6	18.3	17.7	17.2	16.9	16.4	15.8	14.9	11.7	10.2	10.2	8.62	8.00				
85	16.8	16.8	16.8	16.6	16.0	15.6	15.5	15.1	14.5	13.5	11.8	10.6	11.4	9.50	6.09				
90	15.0	15.1	15.1	14.9	14.4	14.1	14.1	13.8	13.3	12.8	12.2	11.5	10.6	9.81	6.53				
95	17.1	17.1	17.1	16.8	16.1	15.7	15.2	14.7	14.3	13.7	12.9	10.1	8.58	10.2	7.23				
100	19.1	19.2	19.2	18.8	17.8	17.3	16.5	15.6	15.4	14.7	13.8	9.96	8.96	7.73	7.17				
105	21.2	21.2	21.3	20.8	19.8	18.9	17.9	16.7	16.5	16.0	15.3	14.7	14.2	13.3	12.7				
110	23.3	23.2	23.4	22.9	21.9	20.5	19.7	18.2	18.0	17.8	17.5	17.3	16.6	15.8	15.2				
115	25.4	25.2	25.6	25.1	24.2	23.0	23.0	22.4	21.8	20.1	20.0	20.0	19.8	18.6	17.9				
120	27.9	27.9	28.5	28.5	28.3	27.8	27.1	26.7	26.6	25.0	23.6	23.7	22.5	21.6	20.7				
125	32.4	32.3	32.4	32.3	32.5	32.4	31.8	30.7	29.5	28.4	27.9	26.7	25.5	24.6	23.7				
130	36.9	36.9	36.7	36.2	36.4	36.3	35.7	34.6	33.4	32.2	30.8	30.0	29.1	28.0	27.1				
135	41.6	41.7	41.5	41.1	40.6	40.1	39.7	38.9	38.0	37.0	35.8	34.7	33.8	32.6	31.7				
140	46.9	47.0	46.9	46.5	45.9	45.0	44.0	44.1	43.9	43.3	42.5	41.6	40.3	39.1	38.4				
145	52.3	52.4	52.4	52.2	51.9	52.2	52.3	52.0	51.6	51.0	50.9	50.0	48.8	48.0	47.7				
150	58.7	59.4	60.2	60.9	61.6	62.1	62.3	62.4	62.3	62.2	61.2	59.7	58.7	58.1	58.0				
155	69.3	69.9	70.6	71.2	71.9	72.6	73.2	73.7	74.2	72.9	71.9	71.1	70.6	70.5	70.8				
160	80.0	80.6	81.1	81.8	82.5	83.3	83.5	82.9	82.4	81.9	81.6	81.4	81.5	81.8	82.3				
165	90.1	90.1	90.0	89.9	89.7	89.5	89.4	89.3	89.2	89.3	89.4	89.6	90.0	90.4	91.1				
170	94.2	94.2	94.2	94.3	94.4	94.4	94.5	94.7	94.8	95.0	95.3	95.6	96.0	96.5	97.0				
175	98.3	98.3	98.4	98.5	98.5	98.7	98.8	98.9	99.1	99.3	99.5	99.8	100	100	101				
180	102	102	102	102	102	102	102	102	102	102	102	102	102	102	102				

C Range: 0 - 360DEG

C Interval: 5.0DEG

Test Speed: HIGH

Temperature:30DEG

Operators:WCZ

Test Date:2015-09-09

g Range: 0 - 180DEG

g Interval: 0.5DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275

Humidity:65.0%

Test Distance:6.220m [K=1.0000]

Remarks: