


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 70.99 lm/W			
MODEL	SZ2210428-14432E-10	I _{max} (cd)	471.8	S/MH(C0/180)	1.27
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	1.12
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	1541.8	η UP,DN(C0-180)	6.4,55.8
NOMINAL FLUX(lm)	1541.8	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,37.8
LAMPS INSIDE	1	η up(%)	6.4	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	93.6	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	451.6	465.8	471.0	465.1	450.2	436.0	430.4	436.4	0- 10	43.38	43.38	2.81,2.81
20	430.1	458.1	468.3	456.8	427.8	400.5	390.0	401.5	10- 20	124.7	168.1	10.9,10.9
30	395.1	435.4	449.7	434.1	391.3	353.3	339.8	354.6	20- 30	190.5	358.6	23.3,23.3
40	346.7	398.8	416.6	397.2	342.0	297.1	282.4	298.4	30- 40	232.9	591.5	38.4,38.4
50	285.8	349.1	370.9	347.6	280.7	233.9	221.0	235.6	40- 50	247.0	838.5	54.4,54.4
60	213.5	287.1	313.4	286.1	208.4	166.7	157.6	168.6	50- 60	231.4	1070	69.4,69.4
70	132.4	214.8	246.3	214.7	126.4	98.12	93.77	99.95	60- 70	187.9	1258	81.6,81.6
80	49.45	138.4	175.6	139.1	45.29	35.75	35.57	37.41	70- 80	124.2	1382	89.6,89.6
90	0.1947	82.55	123.6	84.36	0.0471	0.0953	0.1382	0.1176	80- 90	60.71	1443	93.6,93.6
100	0.1490	59.64	98.16	61.49	0.0681	0.1365	0.1831	0.1482	90-100	34.96	1478	95.8,95.8
110	0.1856	41.89	75.09	43.43	0.1098	0.1833	0.2273	0.1938	100-110	25.01	1503	97.5,97.5
120	0.2480	28.81	54.50	30.02	0.1710	0.2424	0.2773	0.2428	110-120	16.96	1520	98.6,98.6
130	0.3674	19.18	37.64	20.09	0.2382	0.2960	0.3216	0.2902	120-130	10.73	1530	99.3,99.3
140	0.5643	12.19	24.18	12.77	0.3033	0.3448	0.3638	0.3338	130-140	6.220	1537	99.7,99.7
150	0.8164	7.205	14.01	7.540	0.3980	0.4234	0.4385	0.4130	140-150	3.210	1540	99.9,99.9
160	0.9871	3.724	6.831	3.767	0.5303	0.5377	0.5471	0.5257	150-160	1.399	1541	100,100
170	0.9777	1.533	2.296	1.276	0.6333	0.6396	0.6479	0.6106	160-170	0.4604	1542	100,100
180	0.8361	0.8553	0.8415	0.7974	0.8362	0.8462	0.8719	0.8220	170-180	0.0895	1542	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 715.06 lm

%lum = 46.4%

%lamp = 46.4%

Conical surface Flux(120deg): 1069.9 lm

%lum = 69.4%


%lamp = 69.4%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:24.9DEG
 Operators:East
 Test Date:2021-05-07

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity:41%
 Test Distance:2.508m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.18	1.18	1.18	1.14	1.14	1.14	1.08	1.08	1.08	1.02	1.02	1.02	.96	.96	.96	.94
1.0	1.01	.96	.92	.98	.94	.90	.92	.89	.86	.87	.85	.82	.83	.80	.78	.76
2.0	.87	.80	.74	.85	.78	.72	.80	.74	.70	.76	.71	.67	.72	.68	.65	.62
3.0	.76	.68	.61	.74	.66	.60	.70	.63	.58	.66	.61	.56	.63	.58	.54	.52
4.0	.67	.58	.51	.65	.57	.50	.62	.55	.49	.59	.53	.48	.56	.51	.46	.44
5.0	.60	.51	.44	.58	.50	.43	.55	.48	.42	.53	.46	.41	.50	.45	.40	.38
6.0	.54	.45	.38	.52	.44	.38	.50	.42	.37	.48	.41	.36	.45	.40	.35	.33
7.0	.49	.40	.33	.47	.39	.33	.45	.38	.32	.43	.37	.32	.41	.35	.31	.29
8.0	.44	.36	.30	.43	.35	.29	.41	.34	.29	.40	.33	.28	.38	.32	.28	.26
9.0	.41	.32	.27	.40	.32	.26	.38	.31	.26	.36	.30	.25	.35	.29	.25	.23
10.0	.37	.29	.24	.37	.29	.24	.35	.28	.23	.34	.27	.23	.32	.27	.23	.21



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.9DEG
 Operators: East
 Test Date: 2021-05-07

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity: 41%
 Test Distance: 2.508m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.339	.193	.061	.330	.188	.060	.313	.180	.057	.297	.171	.055	.283	.164	.053		
2.0	.308	.169	.052	.300	.165	.051	.285	.159	.049	.271	.152	.048	.258	.146	.046		
3.0	.281	.150	.045	.274	.147	.044	.260	.141	.043	.247	.136	.042	.236	.131	.040		
4.0	.257	.133	.039	.250	.131	.039	.238	.126	.038	.227	.122	.037	.216	.117	.036		
5.0	.236	.120	.035	.230	.118	.034	.219	.114	.034	.209	.110	.033	.199	.106	.032		
6.0	.218	.109	.031	.212	.107	.031	.202	.104	.030	.193	.100	.030	.185	.097	.029		
7.0	.202	.100	.028	.197	.098	.028	.188	.095	.027	.180	.092	.027	.172	.089	.026		
8.0	.188	.092	.026	.184	.090	.026	.175	.088	.025	.168	.085	.025	.161	.082	.024		
9.0	.176	.085	.024	.172	.084	.023	.164	.081	.023	.157	.079	.023	.151	.077	.022		
10.0	.165	.079	.022	.161	.078	.022	.155	.076	.021	.148	.074	.021	.142	.071	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.239	.239	.239	.205	.205	.205	.140	.140	.140	.080	.080	.080	.026	.026	.026	
1.0	.232	.205	.181	.198	.176	.156	.136	.121	.108	.078	.070	.063	.025	.023	.020	
2.0	.224	.182	.146	.192	.156	.126	.132	.108	.088	.076	.063	.051	.024	.020	.017	
3.0	.217	.164	.123	.186	.142	.106	.127	.098	.075	.074	.058	.044	.024	.019	.014	
4.0	.209	.151	.107	.179	.131	.093	.123	.091	.066	.071	.053	.039	.023	.017	.013	
5.0	.201	.141	.097	.173	.122	.084	.119	.085	.059	.069	.050	.035	.022	.016	.012	
6.0	.194	.133	.089	.167	.115	.078	.115	.081	.055	.067	.047	.033	.022	.015	.011	
7.0	.187	.126	.083	.161	.109	.073	.111	.077	.052	.065	.045	.031	.021	.015	.010	
8.0	.181	.120	.079	.155	.104	.069	.108	.073	.049	.063	.043	.029	.020	.014	.010	
9.0	.174	.116	.076	.150	.100	.066	.104	.070	.047	.061	.042	.028	.020	.014	.009	
10.0	.169	.111	.073	.145	.097	.064	.101	.068	.045	.059	.040	.027	.019	.013	.009	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm											
NAME: LED Under cabinet Lights					TYPE:N/A			WEIGHT:N/A			
SPEC.:N/A					DIM.: N/A			SERIAL No.:N/A			
MFR.: Maxim Lighting					SUR.:N/A			Shielding Angle:N/A			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		20.2	21.7	20.6	22.0	22.4	21.6	23.1	21.9	23.4	23.7
3H		21.8	23.1	22.2	23.5	23.9	23.8	25.2	24.2	25.6	25.9
4H		22.4	23.7	22.8	24.0	24.4	25.0	26.3	25.4	26.7	27.1
6H		22.8	24.0	23.2	24.4	24.8	26.2	27.4	26.6	27.8	28.2
8H		22.9	24.0	23.3	24.4	24.9	26.8	28.0	27.3	28.4	28.8
12H		22.9	24.0	23.3	24.4	24.9	27.6	28.7	28.0	29.1	29.5
4H	2H	21.2	22.5	21.6	22.9	23.3	22.2	23.5	22.6	23.9	24.3
	3H	23.1	24.2	23.5	24.6	25.0	24.7	25.8	25.2	26.3	26.7
	4H	23.8	24.9	24.3	25.3	25.8	26.0	27.1	26.5	27.5	28.0
	6H	24.4	25.3	24.9	25.8	26.3	27.4	28.4	27.9	28.8	29.3
	8H	24.6	25.4	25.1	25.9	26.4	28.2	29.1	28.7	29.5	30.1
	12H	24.6	25.4	25.2	25.9	26.5	29.0	29.8	29.6	30.3	30.9
8H	4H	24.6	25.4	25.1	25.9	26.4	26.4	27.3	26.9	27.7	28.3
	6H	25.4	26.2	26.0	26.7	27.2	28.1	28.8	28.6	29.3	29.9
	8H	25.8	26.4	26.3	26.9	27.5	29.0	29.6	29.6	30.2	30.8
	12H	26.0	26.5	26.6	27.1	27.7	30.1	30.6	30.7	31.2	31.8
12H	4H	24.7	25.5	25.3	26.0	26.6	26.4	27.2	26.9	27.7	28.3
	6H	25.8	26.4	26.3	27.0	27.5	28.2	28.8	28.7	29.3	29.9
	8H	26.2	26.8	26.8	27.3	28.0	29.2	29.8	29.8	30.3	30.9
Variations with the observer position at spacings:											
S = 1.0H		+ 0.1 / - 0.2					+ 0.1 / - 0.1				
1.5H		+ 0.2 / - 0.4					+ 0.2 / - 0.3				
2.0H		+ 0.2 / - 0.5					+ 0.2 / - 0.4				

CIE Pub.117 Corrected 1542 lm Total Lamp Luminous Flux.(8log(F/F0) = 1.5)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:


```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.9DEG
 Operators: East
 Test Date: 2021-05-07

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.351
 Humidity: 41%
 Test Distance: 2.508m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180(65)av	6991
L_0~180(75)av	5833
L_0~180(85)av	2941
L_90~270(65)av	8288
L_90~270(75)av	9147
L_90~270(85)av	15545
L_45(65)av	7861
L_45(75)av	8105
L_45(85)av	11689

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 24.9DEG
Operators: East
Test Date: 2021-05-07

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity: 41%
Test Distance: 2.508m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.0V I:0.2011A P:21.72W PF:0.9002 Lamp Flux:1541.8x1 lm		
NAME: LED Under cabinet Lights	TYPE:N/A	WEIGHT:N/A
SPEC.:N/A	DIM.: N/A	SERIAL No.:N/A
MFR.: Maxim Lighting	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	458	458	458	458	458	458	458	458	458	458	458	458	458	458	458	458			
5	456	460	464	466	466	466	464	460	456	452	449	447	446	447	449	452			
10	452	459	466	470	471	469	465	458	450	442	436	432	430	432	436	443			
15	443	454	464	470	471	469	463	453	441	429	420	414	412	414	420	430			
20	430	445	458	466	468	465	457	444	428	412	400	393	390	393	401	414			
25	414	433	449	458	461	457	447	432	411	393	378	369	366	370	379	394			
30	395	417	435	446	450	445	434	416	391	370	353	343	340	344	355	371			
35	372	398	419	431	435	430	418	397	368	344	326	315	312	316	328	346			
40	347	375	399	412	417	412	397	374	342	316	297	286	282	287	298	317			
45	317	349	375	391	395	389	374	348	313	285	266	256	252	256	268	287			
50	286	321	349	366	371	365	348	320	281	252	234	224	221	225	236	254			
55	251	289	320	338	344	337	318	288	246	217	201	192	190	193	203	219			
60	214	254	287	307	313	306	286	253	208	181	167	160	158	161	169	183			
65	174	216	252	274	281	273	251	216	169	143	132	126	125	127	134	146			
70	132	176	215	238	246	238	215	176	126	105	98.1	94.7	93.8	95.7	99.9	107			
75	90.0	135	177	202	211	202	176	136	84.9	69.2	65.6	63.9	63.6	64.8	67.4	71.4			
80	49.4	94.6	138	166	176	166	139	95.6	45.3	36.6	35.7	35.5	35.6	36.3	37.4	38.5			
85	15.8	58.7	105	134	144	135	106	60.6	13.9	11.4	12.0	12.2	12.5	13.0	13.3	12.9			
90	0.19	35.9	82.6	113	124	114	84.4	38.4	0.05	0.06	0.10	0.12	0.14	0.13	0.12	0.09			
95	0.13	26.5	70.4	100	111	101	72.2	29.0	0.05	0.08	0.11	0.15	0.16	0.15	0.13	0.09			
100	0.15	20.0	59.6	88.1	98.2	88.9	61.5	22.2	0.07	0.09	0.14	0.17	0.18	0.17	0.15	0.11			
105	0.17	15.5	50.0	76.8	86.3	77.5	51.7	17.3	0.09	0.12	0.16	0.19	0.21	0.20	0.17	0.13			
110	0.19	12.3	41.9	66.1	75.1	67.0	43.4	13.8	0.11	0.14	0.18	0.22	0.23	0.22	0.19	0.15			
115	0.21	9.91	34.9	56.3	64.6	57.0	36.2	11.1	0.14	0.17	0.21	0.24	0.25	0.24	0.22	0.18			
120	0.25	8.09	28.8	47.4	54.5	48.0	30.0	9.08	0.17	0.20	0.24	0.27	0.28	0.27	0.24	0.21			
125	0.30	6.63	23.6	39.4	45.7	40.0	24.7	7.44	0.21	0.23	0.27	0.29	0.30	0.29	0.27	0.24			
130	0.37	5.42	19.2	32.3	37.6	32.9	20.1	6.05	0.24	0.26	0.30	0.31	0.32	0.31	0.29	0.27			
135	0.45	4.46	15.4	26.1	30.5	26.6	16.1	4.91	0.27	0.29	0.32	0.34	0.34	0.33	0.31	0.29			
140	0.56	3.67	12.2	20.7	24.2	21.0	12.8	4.01	0.30	0.32	0.34	0.36	0.36	0.35	0.33	0.32			
145	0.70	3.02	9.48	16.0	18.7	16.3	9.93	3.28	0.35	0.36	0.38	0.40	0.40	0.39	0.37	0.36			
150	0.82	2.46	7.21	12.0	14.0	12.2	7.54	2.63	0.40	0.40	0.42	0.44	0.44	0.43	0.41	0.40			
155	0.92	1.99	5.28	8.66	10.1	8.79	5.31	2.07	0.47	0.47	0.48	0.50	0.50	0.49	0.48	0.46			
160	0.99	1.61	3.72	5.91	6.83	6.00	3.77	1.54	0.53	0.53	0.54	0.55	0.55	0.54	0.53	0.51			
165	1.00	1.33	2.45	3.70	4.21	3.74	2.25	1.19	0.58	0.58	0.59	0.60	0.59	0.58	0.57	0.56			
170	0.98	1.13	1.53	2.07	2.30	2.03	1.28	0.98	0.63	0.63	0.64	0.65	0.65	0.62	0.61	0.60			
175	0.91	0.96	1.08	1.19	1.21	1.01	0.91	0.87	0.72	0.72	0.73	0.74	0.74	0.72	0.71	0.70			
180	0.84	0.84	0.86	0.86	0.84	0.82	0.80	0.78	0.84	0.84	0.85	0.87	0.87	0.86	0.82	0.80			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.9DEG
Operators:East
Test Date:2021-05-07

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.351
Humidity:41%
Test Distance:2.508m [K=1.0000]
Remarks: