CORONA I CHANDELIER W/FAN

60002SN

- ETL/cETL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)

Job Name	;
Job Type	:
Quantity	:
Comments	:



ACCESSORIES (Sold Separately)




FCT6000WT Wall Control


PRODUCT DESCRIPTION

The Corona Chandelier with fan features a cage of artfully bent Satin Nickel that houses the three innovatively curved fan blades. Its streamlined styling is paired with a high-powered LED ring offering additional downlight while circulation the air.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs





MEASUREMENTS

DIMENSIONS : 27.25"D x 19.5"H
CANOPY : 7"D x 2.75"H
HANGING WEIGHT : 15.86 lb

BLADE : 3 Blades with 22" span

BLADE PITCH : Varying BLADE TO CEILING : 11"H

LAMPING

INPUT VOLTAGE : 120

LUMENS : 3895 Rated (2000 Del.)
BULB : 46W PCB LED (Integrated)

: DC Motor

DIMMABLE : Yes
CRI : 80+
COLOR TEMP : 3000K

AIRFLOW

MOTOR TYPE

SPEEDS : 6
AIRFLOW CFM : 5057
ELECTRICITY USE : 31.90W
AIRFLOW EFFICIENCY: 158.5

FINISHES OPTIONS:

Satin Nickel (SN)

MATERIAL:

Steel

Polypropelene Fan Blades Aluminum

INCLUDES

- Wall Mountable Remote Control
- 1 x 6" Downrod

DOWNROD OPTIONS

- 18" (FRD0118SN)
- 24" (FRD0124SN)
- 30" (FRD0130SN)
- 36" (FRD0136SN)

RATINGS:

ETL cETL Dry Location Title 20





ADDITIONAL:

RATED LIFE: 35,000 Hours

OPERATING TEMP: -20° C (-4°), 40°C (104°F)

LIGHTING DIRECTION: Down



WESTERN DISTRIBUTION CENTER (HEADQUARTER)253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | **F**. 626.956.4225 | maximlighting.com