

TULUM | FANDELIGHT

61012 | 61014

- Hand-Woven rattan in Natural matte coating or Dark stained finish
- Outdoor Dark Bronze powder coat on frame
- DC Motor 6-speed fan with reverse function
- White Tunable LED transitions from warm 2700K to Daylight White
- Wall remote included
- Connect to Wifi for smart enabled function
- Outdoor Fan, installed under covered areas



Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____

PRODUCT DESCRIPTION

Hand woven rattan wicker in a natural or darkened finish are shaped into a sloping drum shade with an internal fan and LED light source within them. The contrasting Dark Bronze finish of the metalwork encases an LED ring toward the bottom edge of the shade allowing for a strobe-free light effect directed downward. The surface coatings are rated for outdoor applications so the rattan and the metalwork are purposefully designed for outdoor spaces under covered roofs. Transform your patio with coastal flair and escape the heat with this Fandelight by Maxim.

FCT6100WT (Remote Control)



FANDELIGHT™
 Magnetically Connect to Wall Plate.
 Light Dimming,
 Battery Operated.
 *CCT tuning on select SKU's

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:
 Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs

MEASUREMENTS


MODEL	DIMENSION	BLADES	CANOPY	HANGING WEIGHT
61012	29"W x 18.5"H	3 x 22"	7.5"W x 2.75"H	16.05 lb
61014	36"W x 19.75"H	3 x 28"	7.5"W x 2.75"H	24.25 lb

LAMPING

MODEL	BULB TYPE	LUMENS	INIT. DEL.	DIMMABLE
61012	30W PCB LED, Integrated	3,420	2,220	Remote or Wifi
61014	35W PCB LED, Integrated	3,990	2,500	Remote or Wifi

ENERGY INFORMATION AT HIGH SPEEDS

CRI	COL TEMP.	CFM	EFFICIENCY	ELECTRICITY USE
80+	2700-4000K	2600 CFM	95 CFM / W	27.3W
80+	2700-4000K	2900 CFM	134 CFM / W	21.6W



FINISHES OPTION

- Natural Rattan w/Dark Bronze (NADBZ)
- Dark Rattan w/Dark Bronze (RADBZ)

MATERIAL

Hand Woven Rattan, Steel, ABS

RATINGS

cETLus
 Damp Location



INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118DBZ)
- 24" (FRD0124DBZ)
- 30" (FRD0130DBZ)
- 36" (FRD0136DBZ)

ADDITIONAL

OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
 101 GARDNER PARK | PEACHTREE CITY, GA 30269
 P. 626.956.4200 | F. 626.956.4225 | maximlighting.com