CALIBRO I OUTDOOR SCONCE

86431 | 86433 | 86435

- Aluminum Construction
- 120-277V LED driver
- Dimmable
- CRI 90+
- Black Finish


Job Name	:
Job Type	:
Quantity	:
Comments	:





PRODUCT DESCRIPTION

Reducing the scale of the classic cylinder sconce is intended for use in applications needed to meet ADA requirements. The sconce profiles extend vertically casting ample light both upwards and downwards. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications.



MEASU	HANGING		
MODEL	DIMENSION	BACK PLATE	WEIGHT
86431	2.5"W x 7.5"H x 3.25"Ext	4.5"W X 4.5"H X 3.75"HCO	2 lb
86433	2.5"W x 14.5"H x 3.25"Ext	4.5"W X 4.5"H X 7.25"HCO	2.74 lb
86435	2.5"W x 19.75"H x 3.25"Ext	4.5"W X 4.5"H X 9.75"HCO	3.3 lb

LAMPING		LUMENS		
MODEL	BULB TYPE	RATED	DEL.	INPUT
86431 86433	2 x 7W (14W Total) LED DC Integrated 3000K 2 x 7W (14W Total) LED DC Integrated 3000K			
	2 x 7W (14W Total) LED DC Integrated 3000K	,		

FINISHES OPTION



MATERIAL

Aluminum, Glass

RATINGS

cETLus Wet Location ADA







ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

