

# COUNTERMAX 5K I UNDERCABINET 5K

89862/ 89863/ 89864/ 89865/ 89866/ 89867

- 5 Color Temperature Options: 5000K, 4000K, 3500K, 3000K, 2700K
- CRI 90+
- Dimmable using Triac and Electronic Low Voltage Dimmers
- Rated life 40,000 hours
- Linkable end to end or with MX interlink cord
- Link up to 750 max watts from one power supply
- 120° rotation

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments: \_\_\_\_\_




## PRODUCT DESCRIPTION

Switch between 5 color temperatures: 5000K, 4000K, 3500K, 3000K, and 2700K. All in 90 CRI for accurate color rendering. The 5K has a patented gimbal designed to allow light to be directed where desired.



- Patent gimbal to direct illumination



## MEASUREMENTS

MODEL	DIMENSION	CRI	HCO
89862	6" L x 3.5" W x 1" H	90+	0.75
89863	12" L x 3.5" W x 1" H	90+	0.75
89864	18" L x 3.5" W x 1" H	90+	0.75
89865	24" L x 3.5" W x 1" H	90+	0.75
89866	30" L x 3.5" W x 1" H	90+	0.75
89867	36" L x 3.5" W x 1" H	90+	0.75

## LAMPING

MODEL	BULB TYPE	COLOR TEMPERATURE	LUMENS RATED	DEL	INPUT	DIMMABLE
89862	3W LED (Integrated)	5000K	360	198	120V	Triac C/L
89863	6W LED (Integrated)	5000K	720	460	120V	Triac C/L
89864	10W LED (Integrated)	5000K	1200	930	120V	Triac C/L
89865	13W LED (Integrated)	5000K	1560	1150	120V	Triac C/L
89866	15W LED (Integrated)	5000K	1800	1420	120V	Triac C/L
89867	19W LED (Integrated)	5000K	2220	1730	120V	Triac C/L

## INCLUDES

- 3/8" knockouts on back and bottom
- Romex connector
- Mounting screws

Always consult a qualified electrician before installing any lighting product

## OPTIONAL



**MXInterLink4 Connector Cord**  
 9" 87876 BK, WT  
 12" 87875 BK, WT  
 18" 87877 BK, WT  
 24" 87878 BK, WT



**Plastic Wire Clip**  
 53255  
 1" L x .5" W x .25" H  
 • Package of 10



**MXInterLink4 Power Cord**  
 87880 BK, WT  
 72" L



**MXInterLink4 Direct Wire Box**  
 87885 BK, WT  
 6.5" L x 2.75" W x 1" H

## FINISHES OPTION

- Bronze
- Satin Nickel
- White

## MATERIAL

Aluminum + LED + PC

## AVAILABLE SIZE:

6" | 12" | 18" | 24" | 30" | 36"

## RATINGS

- cETLus
- Dry Location Energy Star
- JA 8 Listed



## ADDITIONAL

RA TED LIFE 40000 Hours  
 O PERA TING TEMPERA TURE:  
 -20°C (-4°F), 40°C (104°F)



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

**EASTERN DISTRIBUTION CENTER**  
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com