




PRODUCT NAME : Kinetic LED 1-Light Large Pendant
ITEM NUMBER: 39699CLDSN

Please consult your electrician for hanging fixture and wiring.



The fixture is designed to dim with a standard Triac forward phase dimmer. Dimming levels will vary by dimmer.

Below is a list of recommended dimmers:

Voici une liste de variateur recommandé :

Lutron MACL-153M

Lutron DVL-153P

Lutron SCL-153P

Leviton IPL06-10Z

Leviton 6674-POW


Due to inrush current wattage should not exceed 150 watts of product for a 600 watt dimmer.


WARNING: Wires need to be connected to driver found in canopy and should not be connected directly to power source or a short may occur.


Bulb(included) 1-PCB-10W

IMPORTANT: Turn off the power at the main fuse or circuit breaker box before starting installation


(A) 
Mounting Bracket

(B) 
Canopy


(C) 
Metal Part(2PCS)

(D) 
Rods(1*6"+3*12")

Locate all hardware & components before discarding packaging




1.)



step1: Remove mounting bracket from canopy.

2.)




step2: Carefully remove packaging from fixture. Run wire through stems (D) and combine stem lengths to meet desired mounting height. Then attach canopy (B) to fixture.

Cleaning & Care:


Clean with soft cloth and a mild detergent.

Do not use abrasive cleaner.


IMPORTANT: Turn off the power at the main fuse or circuit breaker box before starting installation

(E) 
Canopy (2PCS)


(F) 
Anchor(3PCS)

(G) 
Glass Shade(1PCS)

Locate all hardware & components before discarding packaging




1.)



step3: Install fixture to bracket and tighten ball nuts at the ends of the canopy to secure.

2.)



step4: Lock the glass shade(G) with screws(F)

Cleaning & Care:
Clean with soft cloth and a mild detergent.
Do not use abrasive cleaner.