

PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.

MEASUREMENTS

DIMENSION : 7" W x 4.5" H x 3.5" Ext

BACK PLATE : 2.25" HCO HANGING WEIGHT : 1.51 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 880 Rated (820 Del.)

BULB : 1 x 15W LED PCB Integrated , 15W Total

BULB INCLUDED : (Integrated)

DIMMABLE : Only at 120V with ELV

CRI : 80 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION: Down

FINISHES OPTION

Black (BK) Bronze (BZ)

Silver (SV)

MATERIAL

Aluminum +Acrylic

RATINGS

cETLus Wet Location ADA









ADDITIONAL

INSTALL UP/DOWN: Down **PHOTOCELL** RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746