Pathfinder | 52526SV

Job Name:_

Quantity:







PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

MEASUREMENTS

| DIMENSION | : 5" W x 12" H x 4" Ext |
|--------------------|---|
| BACK PLATE | : 5" W x 12" H x 6" HCO |
| HANGING WEIGHT | : 3.3 lb |
| LAMPING | |
| INPUT VOLTAGE | : 120-277V |
| LUMENS | : 2,500 Rated (1,150 Del.) |
| BULB | : 1 x 25W LED DC Integrated , 25W Total |
| BULB INCLUDED | : (Integrated) |
| DIMMABLE | : Triac or ELV at 120V |
| CRI | : 90 CRI |
| COLOR_TEMP | : 22-27-30-35-40K |
| LIGHTING_DIRECTION | l : Down |
| | |

FINISHES OPTION



MATERIAL Aluminum, Glass

RATINGS

cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com