

CHIP | RD FLUSH MOUNT

57590 | 57591 | 57593 | 57594 | 57596 | 57597


Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____

- Size options: 5.5," 6," 7," 9," and 11"
- Available in 3000K (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in Black (BK), Satin Nickel (SN) and White (WT)
- Dimmable with Triac and ELV Dimmers
- Pendant light accessory available (sold separately)
- Easy to install: fits in 3-0 and 4-0 Outlet Box (Pancake and mud ring acceptable)
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- IP54 Rating



PRODUCT DESCRIPTION

This low profile flush mount is our entry level Wafer. Manufactured of a plastic shell with aluminum backing, the Chip brings all the look of the Wafer at economical pricing for residential applications. The bright and even lighting effect is delivered by edge-lit technology offering an upscale surface mount solution to substitute recessed can lighting. Use the optional pendant adapter to convert any size to a hanging fixture.



MEASUREMENTS

MODEL	DIMENSION
57590	5.5"W x 1.25"H x 5.5)L
57591	5.75"W x 0.75"H x 5.75)L
57593	7"W x 0.75" H x 7)L
57594	9"W x 1.25" H x 9)L
57596	11.25"W x 0.75" H x 11.25)L
57597	11.25"W x 0.75" H x 11.25)L

LAMPING

MODEL	DIMENSION	BULB TYPE	COL	TEMP.	LUMENS	DIMMABLE	INPUT
57590	5.5"W x 1.25"H x 5.5)L	11W PCB Integrated LED	90+	3000K	700	Triac CL/ELV	120V
57591	5.75"W x 0.75"H x 5.75)L	12W PCB Integrated LED	90+	27-30-35-40-50K	700	Triac CL/ELV	120V
57593	7"W x 0.75" H x 7)L	16W PCB Integrated LED	90+	27-30-35-40-50K	950	Triac CL/ELV	120V
57594	9"W x 1.25" H x 9)L	18W PCB Integrated LED	90+	3000K	1200	Triac CL/ELV	120V
57596	11.25"W x 0.75" H x 11.25)L	26W PCB Integrated LED	90+	3000K	1500	Triac CL/ELV	120V
57597	11.25"W x 0.75" H x 11.25)L	26W PCB Integrated LED	90+	27-30-35-40-50K	1500	Triac CL/ELV	120V

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

Satin Nickel (SN)



White (WT)



Black (BK)



MATERIAL:
Polycarbonate + Steel

GLASS:
White

AVAILABLE SIZE:
5.5" | 6" | 7" | 9" | 11"

RATINGS:

cETLus
Wet Location
Title 24
JAB Compliant
ADA



ADDITIONAL:

INSTALL UP/DOWN: UP
RATED LIFE: 50,000 hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)
WIRE LENGTH 8'L



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com