CHIP | FLUSH MOUNT

57690 | 57692 | 57694 | 57695 | 57696 | 57697 | 57698 | 57699

- Size options: 5", 6.5", 7", 9", 12", and 16"
- Available in 3000K (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in Black (BK), Satin Nickel (SN) and White (WT)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- IP54 Rating

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____




Round




Square

PRODUCT DESCRIPTION

This low profile flush mount is our entry level Wafer. Manufactured of a plastic shell with aluminum backing, the Chip brings all the look of the Wafer at economical pricing for residential applications. The bright and even lighting effect is delivered by edge-lit technology offering an upscale surface mount solution to substitute recessed can lighting. Use the optional pendant adapter to convert any size to a hanging fixture.





MEASUREMENTS

MODEL				CRI	COL TEMP.	LUMENS DEL	DIMMABLE	INPUT
57690	RD	5.25"W x 0.75"H x 5.25"L	12W PCB Integrated LED	90+	3000K	950	Triac CL/ELV	120V
57692	RD	7"W x 0.75"H x 7"L	16W PCB Integrated LED	90+	3000K	1200	Triac CL/ELV	120V
57694	RD	9" W x 0.75" H x 9"L	18W PCB Integrated LED	90+	3000K	1500	Triac CL/ELV	120V
57696	RD	12' W x 1" H x 12"L	22W PCB Integrated LED	90+	3000K	1750	Triac CL/ELV	120V
57698	RD	16" W x 1" H x 16"L	32W PCB Integrated LED	90+	3000K	2400	Triac CL/ELV	120V
57695	SQ	5"W x 0.75"H x 5"L	12W PCB Integrated LED	90+	3000K	950	Triac CL/ELV	120V
57697	SQ	6.4"W x 0.75"H x 6.4"L	15W PCB Integrated LED	90+	3000K	1200	Triac CL/ELV	120V
57699	SQ	8.5" W x 0.75" H x 8.5"L	18W PCB Integrated LED	90+	3000K	1500	Triac CL/ELV	120V

FINISHES OPTIONS:

Satin Nickel (SN)

White (WT)

Black (BK)

MATERIAL:

Polycarbonate + Steel

GLASS:

White

AVAILABLE SIZE:

5" | 6.5" | 7" | 9" | 12" | 16"

RATINGS:

cETLus
Wet Location
Title 24
JA8 Compliant
ADA

ADDITIONAL:

INSTALL UP/DOWN: UP
RATED LIFE: 50,000 hours
OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)
WIRE LENGTH 8"L

Always consult a qualified electrician before installing any lighting product

MAXIM® LIGHTING

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 I F. 626.956.4225 I maximlighting.com