


# WAFER LED | SURFACE MOUNT

## 57710 / 57712 / 57714 / 57780 / 57784

- Die Cast Aluminum
- Size options between 5", 7" and 10"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), Black (BK), and Satin Nickel (SN)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_



**57780WT**  
Empty Shell for 7" Round Wafer




**57784WTWT**  
Wafer LED 7" RD w/ 1.5 hours  
Emergency Back Up



### PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

Installs into 3.25" and 4" electrical box with a minimum 2.5" depth



### MEASUREMENTS

#### MODEL DIMENSION

57710	5"D x 0.5"H
57712	7"D x 0.5"H
57780	7"D x 1.25"H
57784	7"D x 1.75"H
57714	10"D x 0.5"H

#### HANGING WEIGHT

0.88 lb
1.21 lb
1.75 lb

### LAMPING

#### MODEL BULB TYPE

*57710	10W LED (Integrated)
*57712	15W LED (Integrated)
*57780	Add on shell
*57784	15W LED (Integrated)
*57714	20W LED (Integrated)

CRI	LUMENS	INIT DEL	COL TEMP.	DIMMABLE	INPUT
90+	700	600	3000K	ELV	120V
90+	1050	900	3000K	ELV	120V
90+	1100	900	3000K	ELV	120V
90+	1400	1200	3000K	ELV	120V

\*120-277V input and 0-10V dimming available upon request

Always consult a qualified electrician before installing any lighting product

### FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Black (BK)
- Satin Nickel (SN)



### MATERIAL:

Die Cast Aluminum  
PMMA Acrylic Diffuser

### AVAILABLE SIZES:

5" | 7" | 10"

### RATINGS:

ETL/cETL IP65  
Wet Location  
Title 24 JA8 compliant  
ADA  
Dimmable  
Closets Rated: 410.8 & 410.16



### ADDITIONAL:

RATED LIFE: 50,000 Hours  
OPERATING TEMP: -20° C (-4°), 40° C (104° F)  
PHOTOMETRIC: Report Found Online



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

**EASTERN DISTRIBUTION CENTER**  
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com