

WAFER LED 15" I SURFACE MOUNT

57736


- Edge-Lit Technology, evenly distributed light
- Available in 3000K color temperature (See 57737 for 4000K)
- Available in Bronze (BZ), Satin Nickel (SN), and White (WT)
- Dimmable with ELV dimmer at 120V
- 120-277 Input Voltage
- Easy to install: Fits 4" Outlet Box (Pancake NOT recommended)
- Approved for use in closets and storage spaces
- Suitable for Wet location
- ETL/cETL IP65

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS


DIMENSIONS : 15"L x 15"W x 0.5"H
HANGING WEIGHT : 3.53 Lb MAX OH : 0.5"
HCO : 0.5" MIN OH : 0.5"
BP Width : 4.1"

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 2500 Rated (2200 Del.)
BULB : (1) 36W PCB LED (Integrated)
DIMMABLE : Dimmable with ELV Dimmer at 120V
CRI : 90+
COLOR TEMPERATURE: 3000K

FINISHES OPTIONS:

White (WT)
Bronze (BZ)
Satin Nickel (SN)



MATERIAL:

Aluminum
PMMA Acrylic Diffuser

RATINGS:

ETL/cETL IP65
Wet Location
J8 Title 24



ADDITIONAL:

RATED LIFE: 40,000 Hours
OPERATING TEMP: -20° C (-4°), 40° C (104° F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com