

WAFER LED LINEAR | SURFACE MOUNT

57746 / 57747


- Edge-Lit Technology
- Aluminum extruded body for better heat dissipation
- Available in 3000K / 4000K color temperature
- Dimmable with ELV dimmer at 120V
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- 120-277 Input Voltage
- Easy to install: Fits 4" Outlet Box
- Not recommended for pancake box
- Suitable for Wet location
- ETL/cETL, IP65

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

DIMENSIONS : 48"L x 4.5"W x 0.5"H
HANGING WEIGHT : 3.97 lb MAX OH : 0.5"
HCO : 0.5" MIN OH : 0.5"
BP Width : 4.1"

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 3200 Rated (2500 Del.)
BULB : 36W PCB LED (Integrated)
DIMMABLE : ELV Dimmer at 120V
CRI : 90+

Model	Color Temp.
57746	3000K
57747	4000K

FINISHES OPTIONS:

White (WT)



MATERIAL:

Aluminum
PMMA Acrylic Diffuser

RATINGS:

Closets Rated: NEC 410.8 & 410.16
ETL/cETL IP65
Wet Location



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40° C (104° F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com