
WAFER LED I SURFACE MOUNT

57710 / 57712 / 57714 / 57780 / 57784

- Die Cast Aluminum
- Size options between 5", 7" and 10"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____





57780WT
Empty Shell for 7" Round Wafer



57784WTWT
Wafer LED 7" RD w/ 1.5 hours Emergency Back Up

PRODUCT DESCRIPTION


Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

FINISHES OPTIONS:

White (WT)
Bronze (BZ)
Satin Nickel (SN)



Installs into 3.25" and 4" electrical box with a minimum 2.5" depth



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT
57710	5"D x 0.5"H	0.88 lb
57712	7"D x 0.5"H	1.21 lb
57780	7"D x 1.25"H	
57784	7"D x 1.75"H	
57714	10"D x 0.5"H	1.75 lb

LAMPING

MODEL	BULB TYPE	CRI	LUMENS INIT	LUMENS DEL	BATTERY BACKUP LUMENS DEL	COL TEMP.	DIMMABLE	INPUT
*57710	10W LED (Integrated)	90+	700	600		3000K	ELV	120V
*57712	15W LED (Integrated)	90+	1050	900		3000K	ELV	120V
*57780	Add on shell							
*57784	15W LED (Integrated)	90+	1100	900	330	3000K	ELV	120V
*57714	20W LED (Integrated)	90+	1400	1200		3000K	ELV	120V

**120-277V input and 0-10V dimming available upon request*

Always consult a qualified electrician before installing any lighting product

MATERIAL:

Die Cast Aluminum
PMMA Acrylic Diffuser

AVAILABLE SIZES:

5" | 7" | 10"

RATINGS:

ETL/cETL IP65
Damp Location
Title 24 JA8 compliant
ADA
Dimmable
Closets Rated: 410.8 & 410.16

ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online

MAXIM LIGHTING

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 I **F.** 626.956.4225 I maximlighting.com