

WAFER LED PENDANTS 15" | SURFACE MOUNT

57836/ 57838

- New models feature 120-277V input
- Ultra thin 0.5" H
- Dimmable with Triac Dimmer, CRI 90+
- 50,000 Hours Rated life, 3000K
- Suitable for Damp location
- ETL/cETL IP65

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____



57836



57838

PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

MEASUREMENTS

DIMENSIONS : 15" L x 15" W x 0.5" H
CANOPY : 6" L x 6" W x 1.5" H
OAH : 122" H
WIRE LENGTH : 120" L

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 2520 Rated (2200 Del.)
BULB : 36W PCB LED (Integrated)
DIMMABLE : Dimmable with ELV Dimmer at 120V
CRI : 90+
COLOR TEMPERATURE: 3000K

FINISHES OPTIONS:

White (WT)
Bronze (BZ)
Satin Nickel (SN)



MATERIAL:

Aluminum
PMMA Acrylic Diffuser

RATINGS:

ETL/cETL IP65
Damp Location
Dimmable



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40° C (104° F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com