


PRODUCT DESCRIPTION

Step and pathway lighting suitable for interior or exterior application. Designed to install into a single gang box and is line voltage so additional transformers are not needed. Available in Aluminum, White, Black, or Bronze and both horizontal wide beam or vertical narrow beam spread.



MEASUREMENTS DIMENSION

MAX OAH

: 3" W x 5" H

LAMPING

LUMENS BULB **BULB INCLUDED**

CRI

: 5" W x 3" H x 1.5" Ext : 0.77 lb

HANGING WEIGHT

- INPUT VOLTAGE

:120V : 280 Rated (112 Del.) : 1 x 4W LED PCB Integrated , 4W Total : (Integrated) DIMMABLE :No : 80+ CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Down

FINISHES OPTION

Black (BK) Bronze (BZ)

Brushed Aluminum (AL)

White (WT)

MATERIAL

Aluminum

RATINGS CETLUS Wet Location



ADDITIONAL INSTALL UP/DOWN: Up

RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com