SOLITAIRE I CHANDELIER W/FAN 60013SM

- ETL/cETL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)
- Frosted CA LED bulbs included



ACCESSORIES (Sold Separately)



FCT6000WT Wall Control

PRODUCT DESCRIPTION

The creme de la creme - the Solitaire. This romantic Chandelier with Fan delivers luxury appeal and timeless sophistication. The Solitaire features curved arms that lift a crown of six candle-style lamps. It is adorned with six large marquise cut crystals and six circular cut crystals that illuminate the surroundings in a regal display of light. This beautiful chandelier with fan is hand-painted in a Silver Mist finish creating a sophisticated wrought-iron appearance.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:
- Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs





MEASUREMENTS

 DIMENSIONS
 : 30.75"D x 18.75"H

 CANOPY
 : 6.75"D x 2.75"H

 HANGING WEIGHT
 : 20.75 lb

 BLADE
 : 3 Blades with 22" span

 BLADE PITCH
 : Varying

 BLADE TO CEILING
 : 9.75"H

:120V

LAMPING

INPUT VOLTAGE LUMENS BULB DIMMABLE CRI COLOR TEMP MOTOR TYPE

: Yes : 80+ : 3000K : DC Motor

: (6) 4W LED (Bulb Included), 24W Total

: 1988 Rated (1680 Del.)

AIRFLOW SPEEDS : 6 AIRFLOW CFM : 5057 ELECTRICITY USE : 31.90W AIRFLOW EFFICIENCY: 158.5



Silver Mist (SM)

Job Name : ____

Quantity :

Job Type : _____

Comments :

MATERIAL:

Steel K9 Crystal Polypropelene Fan Blades

INCLUDES

Wall Mountable Remote Control
 1 x 8" Downrod

DOWNROD OPTIONS

• 18" (FRD0118SM)

- 24" (FRD0124SM)
- 30" (FRD0130SM)
- 36" (FRD0136SM)

RATINGS:

ETL cETL Dry Location Title 20



ADDITIONAL: RATED LIFE: 20,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) LIGHTING DIRECTION: Down

WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746 EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336



