






## PRODUCT DESCRIPTION

Inconspicuously recessed within its cylindrical house, an extending arm transforms this surface mounted light fixture into an adjustable spotlight. Simply unthread the top half along the seam to extend the frame length and swing the fixture into position. Twist the lens on the face of this fixture to adjust its beam angle spread. Available in Black and White and two apertures that include a mud-in ring for an even cleaner installation.



## **MEASUREMENTS**

DIMENSION : 5.25" L x 5.25" W x 3.25" H CANOPY : 5.25" W x 0.25" H x 5.25" L

HANGING WEIGHT : 0.88 lb

**LAMPING** 

INPUT VOLTAGE : 120-277V

LUMENS : 1,200 Rated (1,030 Del.)

BULB : 1 x 12W LED DC Integrated , 12W Total

BULB INCLUDED : (Integrated)

DIMMABLE : Triac or ELV at 120V

CRI : 90 CRI COLOR\_TEMP : 3000K

#### **FINISHES OPTION**



# MATERIAL

Aluminum, Glass

### **RATINGS**

cETLus Dry Location Energy Star CA Title 24







## **ADDITIONAL**

RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com