

# CALIBRO | OUTDOOR SCONCE

86431 | 86433 | 86435


- Aluminum Construction
- 120-277V LED driver
- Dimmable
- CRI 90+

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_



## PRODUCT DESCRIPTION

This classic cylinder design has been made ultra-thin intending its use in applications requiring ADA compliance. The sconce casts generous lighting both upwards and downwards using dedicated, high-powered LED. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications. Available in Matte Black, Architectural Bronze and White outdoor powder coat finishes. For Dark Sky applications, make use of the optional Dark Sky Cap available.






## MEASUREMENTS

MODEL	DIMENSION	BACK PLATE	HANGING WEIGHT
86431	2.5"W x 7.5"H x 3.25"Ext	4.5"W X 4.5"H X 3.75"HCO	2 lb
86433	2.5"W x 14.5"H x 3.25"Ext	4.5"W X 4.5"H X 7.25"HCO	2.74 lb
86435	2.5"W x 19.75"H x 3.25"Ext	4.5"W X 4.5"H X 9.75"HCO	3.3 lb

## LAMPING

MODEL	BULB TYPE	LUMENS		
		RATED	DEL.	INPUT
86431	2 x 7W (14W Total) LED DC Integrated 3000K	1,400	1190	120V-277
86433	2 x 7W (14W Total) LED DC Integrated 3000K	1,400	1190	120V-277
86435	2 x 7W (14W Total) LED DC Integrated 3000K	1,400	1190	120V-277

## FINISHES OPTION

-  Architectural Bronze (ABZ)
-  Black (BK)
-  White (WT)

## MATERIAL

Aluminum, Glass

## RATINGS

cETLus  
 Wet Location  
 ADA



## ADDITIONAL

INSTALL UP/DOWN: Up  
 RATED LIFE 25000 Hours  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)

PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER  
 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com