TANKER | CEILING FAN

88805 | 88806 | 88816 Rated for both Indoor and Outdoor Applications *88816 uses DC Motor to meet **Energy Star Rating** 88806,*88816 BK, SN **ENERGY STAR OPTION** *88816 88805 BK, SN

Job Name : _____ Job Type :_ Quantity: Comments:

BLADE FINISHES





SN w/Silver

BK w/Black

INCLUDED CONTROLS FCT88805WT



3-Speed Fan Control Included with: 88805 & 88807





AC Wall Control Light and Fan Speed On/Off Rocker Switch for Light Switch Included with: 88801,88802,88806

FCT88816WT



DC Wall Remote Light and Fan Speed Control Non-Dimming Included with: 88816

OPTIONAL CONTROLS *Sold Separately

FCT8881WT



AC Wall Control, Light Dimming and Fan Control Compatible with: 88801, 88802, 88806, 89909


FCTHAND



Universal Wall Remote. Compatible with All Fans (Excl. Fandelights)


PRODUCT DESCRIPTION

Clean and contemporary, the Tanker ceiling fan is damp rated so whether it is a covered outdoor living space or any room indoor this sleek fan suits the application. Ditch the fan rod and convert to a hugger. Several lengths of extension rods allow you to use this fan no matter the ceiling height. Available in 2 different finishes: Satin Nickel, and matte Black.



			LUME	ENS			BLADE	
ITEM#	LAMPING	DIMENSIONS	RATED	DEL	WEIGHT	BLADES	PTICH	ADDITIONAL
88805	120V, No Light Kit	D52" X 14.52"H			11.62 lb	3 x ABS (Included)	12	
88806	120V 1 X 24W LED 3000K	D52" X 14.52"H	2100	1680	11.62 lb	3 x ABS (Included)	12	
*88816	120V 1 X 24W LED 3000K	D52" X 14.52"H	2100	1680	11.62 lb	3 x ABS (Included)	12	DC Motor, Energy Sta

Energy Information at High Speeds							
AIRFLOW CFM	AIRFLOW EFFICIENCY	ELECTRICITY USE					
4700 CFM	97 CFM / W	48W					
4700 CFM	97 CFM / W	48W					
4700 CFM	333 CFM / W	13W					



FINISHES:

BLACK (BK) w Black Blades

SATIN NICKEL (SN) w SILVER Blades

MATERIAL

Steel + Aluminum Body **ABS Blades**

RATINGS

cETLus Damp Location

*Energy Star (*88816 Only)









FAN RODS: (SOLD SEPARATELY)

6" x 3 (Incl.)

12" (FRD18)

18" (FRD24)

24" (FRD30)

36" (FRD36)

48" (FRD48) 60" (FRD60)

72" (FRD72)

ADDITIONAL:

RATED LIFE: 50,000 Hours **OPERATING TEMP:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

CONTROLS

Easily adjust the speed and direction of your fan with a wall control. Adjust color temperature using a color tunable fan and wall control.



FCT88801WT

AC Wall Control Light and Fan Speed Controls On/Off Rocker Switch for Light

Included with:

88801,88802,88806



FCT88816WT

DC Wall Remote Light and Fan Speed Control Non-Dimming

Included with:

88816



FCT88805WT

Fan Control Only

Three Speed Fan Control

Included with:

88805 & 88807

OPTIONAL



FCT 8881WT

AC Wall Control Light Dimming and Fan Control *Sold Separately

Compatible with:

88801, 88802, 88806, 89909



FCTHAND

Universal AC Wall Remote *Sold Seperately

Compatible with All Fans (Excl. Fandelights)

FANDELIGHTTM



FCT 6000WT FANDELIGHT™ Wall Remote

Magnetically Connect to Wall Plate Light Dimming Battery Operated

Compatible with:

60002,61004,61009,61013, 61016,61018



FCT 6100WT FANDELIGHT ™ Wall Remote

Magnetically Connect to Wall Plate Light Dimming Battery Operated *CCT tuning on select SKU's

Compatible with:

61002,61006,61010,61012, 61014,61019



WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com