COUNTERMAX MX-L-24-SS | 24V SLIM STICK

89800|89801|89802|89803|89804

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____

- Aluminum finish with Black accessories
- Even distribution of LED diffused through opal white lens
- 24V system must be paired with driver accessories
- Linkable end-to-end or with MX Interlink cord
- Adjustable mounting clips allow for angled installation
- Dimmable with LED dimmers
- Title 24 JA8 listed=
- 3000K Color Temperature
- CRI 90+






- Includes adjustable mounting clips




89835AL *Sold Separately
In-Line Dimmer Switch
On/Off and Brightness Control

PRODUCT DESCRIPTION
Narrow Aluminum channels of LED are easily concealed in an economical way to tackle your task lighting. Installation is simple with an adjustable bracket that allows you to direct the light to where you need it, and a simple plug-in or hard wire power supply. Available in lenghts from 6" to 48" and varies accessories, Slim Stick is the easy solution for your task lighting installation.

LED PROFILE



IN-LINE DIMMER



FINISHES:
ALUMINUM (AL)

MATERIAL
Aluminum

RATINGS
cETLus
Dry Location
JA8 Listed

ADDITIONAL
OPERATING TEMPERATURE: -20° C (-4°F), 40°C (104°F)

MEASUREMENTS

MODEL	DIMENSION
89800	0.75"W x 0.5"H x 6"L
89801	0.75"W x 0.5"H x 12"L
89802	0.75"W x 0.5"H x 24"L
89803	0.75"W x 0.5"H x 36"L
89804	0.75"W x 0.5"H x 48"L

LAMPING

BULB TYPE	COLOR TEMP	CRI	LUMENS RATED	LUMENS DELIVERED	DIMMABLE	V INPUT
3W Integrated LED	3000K	90+	350	195	LED	24V
5W Integrated LED	3000K	90+	700	395	LED	24V
10W Integrated LED	3000K	90+	1050	780	LED	24V
15W Integrated LED	3000K	90+	1400	1170	LED	24V
20W Integrated LED	3000K	90+	1750	1560	LED	24V

(SEE COMPATIBLE DRIVERS AND ACCESSORIES ON NEXT PAGE FOR DIMMING INFORMATION)

Always consult a qualified electrician before installing any lighting product.

MAXIM® LIGHTING

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 I F. 626.956.4225 I maximlighting.com

24V CONSTANT VOLTAGE LED DRIVERS


Hard Wired Power Supplies



Hard Wired Driver

DHW898-2496BK
W8.5" H3.25"

100-295V input
96W MAX
Includes Plug in Connector
Compatible with Triac or ELV



Dimmable Driver Switch

SWT898-2460WT
60W MAX
SWT898-2475WT
75W MAX
2"W **x** 2.25"L x 4.25"H

Plug-in Power Supplies

*can be used with in-line dimmer switch



89811BK
24W Plug-In Driver Non-dimming



DRV898-2460BK (89812BK)
60W Plug-In Driver Non-Dimming



89814BK
96W Plug-In Driver Non Dimming



89835AL
In-Line Dimmer Switch
On/Off and Brightness Control

CONNECTING CORDS



89822BK 12"
*includes
ON/OFF switch



CRD898-18BK
18"



CRD898-36BK
36"



CRD898-60BK
60"



89833BK
LOW VOLTAGE SPLICE BOX
L 1.75" x W 2.25" x H 0.5"



90° CONNECTOR

89830BK
L

89831BK
R

Always consult a qualified electrician before installing any lighting product.

MAXIM® LIGHTING

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 I F. 626.956.4225 I maximlighting.com