COUNTERMAX 5K I UNDERCABINET 5K

89862 / 89863 / 89864 / 89865 / 89866 / 89867


Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____

- 5 Color Temperature Options: 5000K, 4000K, 3500K, 3000K, 2700K
- CRI 90+
- Dimmable using Triac and Electronic Low Voltage Dimmers
- Rated life 35,000 hours
- Linkable end to end or with MX interlink cord
- Link up to 750 max watts from one power supply
- 120° rotation
- Suitable for Closets according to NEC Section 410.8 & 410.16(C) 5



PRODUCT DESCRIPTION

Switch between 5 color temperatures: 5000K, 4000K, 3500K, 3000K, and 2700K. All in 90 CRI for accurate color rendering.



MEASUREMENTS

MODEL	DIMENSION	CRI
89862	6"L x 3.5" W x 1"H	90+
89863	12"L x 3.5" W x 1"H	90+
89864	18"L x 3.5" W x 1"H	90+
89865	24"L x 3.5" W x 1"H	90+
89866	30"L x 3.5" W x 1"H	90+
89867	36"L x 3.5" W x 1"H	90+

LAMPING

MODEL	BULB TYPE	COLOR TEMPERATURE	LUMENS RATED	LUMENS DEL	INPUT	DIMMABLE
89862	3W LED (Integrated)	27-30-35-40-50 K	270	198	120V	Triac or ELV
89863	6W LED (Integrated)	27-30-35-40-50 K	540	460	120V	Triac or ELV
89864	9W LED (Integrated)	27-30-35-40-50 K	1100	930	120V	Triac or ELV
89865	12W LED (Integrated)	27-30-35-40-50 K	1400	1150	120V	Triac or ELV
89866	15W LED (Integrated)	27-30-35-40-50 K	1600	1420	120V	Triac or ELV
89867	18W LED (Integrated)	27-30-35-40-50 K	1900	1730	120V	Triac or ELV

INCLUDES

- 3/8" knockouts on back and bottom
- Romex connector
- Mounting screws

Always consult a qualified electrician before installing any lighting product

OPTIONAL



MXInterLink4 **Connector Cord**
9" **87876 BK**, WT
12" **87875 BK**, WT
18" **87877 BK**, WT
24" **87878 BK**, WT



Plastic Wire Clip
53255
1"L x .5"W x .25"H
• Package of 10



MXInterLink4 **Power Cord**
87880 BK, WT
72"L



MXInterLink4 **Direct Wire Box**
87885 BK, WT
6.5"L x 2.75"W x 1"H

FINISHES OPTION

Bronze (BZ)
Satin Nickel (SN)
White (WT)

MATERIAL

Aluminum + PC

AVAILABLE SIZE:

6" | 12" | 18" | 24" | 30" | 36"

RATINGS

cETLus
Damp Location
CA Title 24

ADDITIONAL

INSTALL UP/DOWN: Down
RATED LIFE 35000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

MAXIM LIGHTING®

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 I F. 626.956.4225 I maximlighting.com