LED RN BULB I BULBS

Job Name : _ BUL-3.5W-ST64-E26-CL-120V-822 | BUL-3.5W-D40-E26-CL-120V-822 BUL-3.5W-G40-E26-CL-120V-822 | BUL-3.5W-G40-E26-PR-120V-822 Job Type : _ BUL-3.5W-A52-E26-CL-120V-822 Quantity : ____ • Available in 2200K color temperature Comments : • Dimmable with Flicker Free • 110-130 Input Voltage • Rated life 25,000 lifetime hours • 3.5W, 150 Lumens • ETL/cETL **ST64** D40 G40 CL G40 PR A52

PRODUCT DESCRIPTION

An innovative acrylic light tower is laser etched to create the effect of a filament bulb. Choose from varying styles that can be installed on any medium base socket. Bulb types range from everyday shapes, such as ST64 or G40, and includes large scale A52 glass types, interesting diamond shapes, and patterned glasses. The glass is hardened making it more durable than average bulbs creating the most robust LED bulbs on the market.



BULB TYPE: ST64 MEASUREMENTS DIMENSIONS : 2.5"D x 5.5"H

HANGING WEIGHT : 0.19 lb

MATERIAL GLASS: Clear



BULB TYPE: G40 MEASUREMENTS

DIMENSIONS : 5"D x 6.5"H HANGING WEIGHT : 0.42 lb

MATERIAL GLASS: Clear



BULB TYPE: D40 MEASUREMENTS

DIMENSIONS : 5"D x 7"H HANGING WEIGHT : 0.44 lb

MATERIAL GLASS: Diamond

BULB TYPE: G40 MEASUREMENTS

DIMENSIONS : 5"D x 6.5"H HANGING WEIGHT : 0.44 lb

MATERIAL GLASS: Prismatic

H

BULB TYPE: A52

MEASUREMENTS DIMENSIONS : 6.5"D x 12"H HANGING WEIGHT : 1.12 lb

MATERIAL GLASS: Fluted LAMPING WATTAGE : 3.5W INPUT VOLTAGE : 110-130V LUMENS : 150 COLOR TEMP. : 2200K BASE TYPE : E26 DIMMABLE : Flicker free Dimming

н

RATINGS: ETL/CETL Title 20 Exempt

۲.

ADDITIONAL: RATED LIFE: 25,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com